

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2351 Walnut Hill Lane Suite 150 75229-0000, TX Dallas Phone: 214-351-0785 Fax: 972-241-1564

Catalog Numbor	& AF30301113
Catalog Number Manufacturer	Industrial Connections &
Description	AF30 Contactors Are Used For Controlling Power Circuits Up to 690 V Ac and 220 V DC. They Are Mainly Used For Controlling 3-Phase Motors, Non-Inductive or Slightly Inductive Loads. Af Contactors Include An Electronic Coil Interface Accepting A Wide Control Voltage Uc Min Uc Max. Only Four Coils Cover Contro Voltages Between 24500 V 50/60 HZ or 20500 V DC. Af Contactors Can Manage Large Control Voltage Variations. One Coil Can Be Used For Different Control Voltages Used Worldwide Without Any
Weight per unit	0.8500 (lbs/each)
Product Category	IEC Contactors
escriptions	
Description	AF30-30-11-13 100-250V50
extra long description	ABB AF30-30-11-13 AF30-30-11-13 100
Long Description	AF30 contactors are used for controlling power circuits up to 690 V AC and 220 V DC. They are mainly used for controlling 3-phase motors, non-inductive or slightly inductive loads. AF contactors include an electronic coil interface accepting a wide control voltage Uc min Uc max. Only four coils cover control voltages between 24500 V 50/60 Hz or 20500 V DC. AF contactors can manage large control voltage variations. One coil can be used for different control voltages used worldwide without any
Product Type	AF30-30-11-13 100-250V50/60HZ-DC CO
lanufacturer Information	
Brand	ABB
GTIN	00888614244276
Manufacturers Part Number	AF30-30-11-13
UPC	888614244276
axonomies, Classifications, and (Categories
	IEC/FREEDOM CONTACTOR
ackaging	
Carton	1
Weight Per each	0.85