



AG3000 120/240VAC 1PH 3-Mode Hvac Surge Protective Device

Intermatic Inc.

Catalog Number	AG3000
Manufacturer	Intermatic Inc.
Description	Surge Protective Device, 3-Mode, 120/240 Vac 1PH, Type 1 or Type 2, Outdoor, Connected Equipment Warranty 3YR \$7,500
Weight per unit	0.6500 (lbs/each)
Product Category	Surge Suprsr-Prot Dev-LN Condi

Features

connection	Lead
Enclosure Type	Type 4X
Material	Polycarbonate
nominal discharge current	10
Phase	1
Poles	3
type of indicators	Green LED
Voltage Rating	120/240 VAC
wiring configuration	L1, L2, L/N-G

Dimensions and Weight

Size	1/2 IN - 20
------	-------------

Descriptions

Description	120/240VAC 1PH 3-MODE HVAC SURGE PROTECTIVE DEVICE
extra long description	INT-MAT AG3000 Surge Protective Dev
Features	Power surges are the silent killer for home appliances and HVAC equipment. Most homeowners protect their electronics, but leave more valued equipment unprotected. Surges can wipe out equipment and leave you searching for answers. Search no more. The easy-to-install AG3000 Surge Protective Device (SPD) is the perfect add-on for HVAC equipment. A green LED indicator provides the status of protection. Trusted, state-of-the-art TPMOV® (Thermally Protected Metal Oxide Varistor) technology eliminates the potent
Long Description	Surge Protective Device, 3-Mode, 120/240 VAC 1Ph, Type 1 or Type 2, Outdoor, Connected Equipment Warranty 3yr \$7,500
Product Type	Surge Protective Device, 3-Mode, 120/240 Vac 1PH, Type 1 or
Special Features	Features: LED Indicator provides Status;UV Resistant



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

149 North Wilson St.
76028-0000, TX Burleson
Phone: 817-447-0192
Fax: 817-426-1193

Manufacturer Information

Brand	Intermatic
GTIN	00078275130678
Manufacturers Part Number	AG3000
series	AG
UPC	078275130678

Taxonomies, Classifications, and Categories

Category Description	SURGE SUPPRESSION PRODUCTS
Type	Type 1/Type 2 Surge Protective Device

Packaging

Carton	1
Package	8
Weight Per each	0.65

Uses, Certifications, and Standards

Application	HVAC Equipment (AC/Furnaces)
environmental conditions	-4 to +104 DEG F, -20 to +40 DEG C
standard	CSA - UL 1449 3rd Edition