



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



AH430R5W Recp Pin & Sleeve 30A 600V 3PH 3P4W *Eaton Wiring Devices*

Catalog Number	AH430R5W
Manufacturer	Eaton Wiring Devices
Description	Eaton Arrow Hart Pin and Sleeve Receptacle, IP69K Rated, #10 -#2 Awg, 30A, 3Ø 600V, Back Wire, Black, Nickel Plated Brass, IP67, Nylon, Three-Pole, Four-Wire, Grounding, AHBB30 Back Box Style, Female, 15 HP, Nylon, Three-Phase
Weight per unit	32.0 (lbs/each)
Product Category	Gen Purpose Recept & Surge Pro

Features

dimensions	3.7500 IN X 4.2100 IN X 3.1250 IN
media	Yes

Descriptions

Description	RECP PIN & SLEEVE 30A 600V 3PH 3P4W
extra long description	EWD AH430R5W 30A,3PH 600V 3P4W PIN+
Features	Eaton's Arrow Hart full line of pin and sleeve devices offer sturdy nylon construction, rugged design with corrosion resistant components for lasting electrical performance, and watertight sealing that provides IP69K protection so you can feel confident in even the most severe washdown environments.
Long Description	Eaton Arrow Hart pin and sleeve receptacle, IP69K Rated, #10 -#2 AWG, 30A, 3Ø 600V, Back wire, Black, Nickel plated brass, IP67, Nylon, Three-pole, Four-wire, grounding, AHBB30 Back box style, Female, 15 HP, Nylon, Three-phase
Product Type	30A, 3PH 600V 3P4W Pin+Sleeve Receptacle
Special Features	Watertight P&S receptacles

Manufacturer Information

Brand	Eaton
GTIN	00326647319696
Manufacturers Part Number	AH430R5W
UPC	032664731969

Taxonomies, Classifications, and Categories

Category Description	Pin & Sleeve Devices
Type	Pin and Sleeve receptacle

Packaging

Carton	1
Package	32
Weight Per each	32



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Uses, Certifications, and Standards

Application
standard

Ind Facilities & Factories - Facility: Power Distribution and Control
cRUus