



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

7520 Eastgate Blvd Suite 100
37122-0000, TN Mt. Juliet
Phone: 615-257-4146
Fax: 615-257-4147



AH430R5W Recept Pin & Sleeve 30A 600V 3PH 3P4W *Eaton Wiring Devices*

| | |
|------------------|--|
| Catalog Number | AH430R5W |
| Manufacturer | Eaton Wiring Devices |
| Description | Eaton Arrow Hart Pin and Sleeve Receptacle, IP69K Rated, #10 -#2 Awg, 30A, 3Ø 600V, Back Wire, Black, Nickel Plated Brass, IP67, Nylon, Three-Pole, Four-Wire, Grounding, AHBB30 Back Box Style, Female, 15 HP, Nylon, Three-Phase |
| Weight per unit | 32.0 (lbs/each) |
| Product Category | Gen Purpose Recept & Surge Pro |

Features

| | |
|-------|-----|
| media | Yes |
|-------|-----|

Descriptions

| | |
|------------------------|--|
| Description | RECP PIN & SLEEVE 30A 600V 3PH 3P4W |
| extra long description | EWD AH430R5W 30A,3PH 600V 3P4W PIN+ |
| Features | Eaton's Arrow Hart full line of pin and sleeve devices offer sturdy nylon construction, rugged design with corrosion resistant components for lasting electrical performance, and watertight sealing that provides IP69K protection so you can feel confident in even the most severe washdown environments. |
| Long Description | Eaton Arrow Hart pin and sleeve receptacle, IP69K Rated, #10 -#2 AWG, 30A, 3Ø 600V, Back wire, Black, Nickel plated brass, IP67, Nylon, Three-pole, Four-wire, grounding, AHBB30 Back box style, Female, 15 HP, Nylon, Three-phase |
| Product Type | 30A, 3PH 600V 3P4W Pin+Sleeve Receptacle |

Manufacturer Information

| | |
|---------------------------|----------------|
| Brand | Eaton |
| GTIN | 00032664731969 |
| Manufacturers Part Number | AH430R5W |
| UPC | 032664731969 |

Taxonomies, Classifications, and Categories

| | |
|----------------------|----------------------|
| Category Description | Pin & Sleeve Devices |
|----------------------|----------------------|

Packaging

| | |
|-----------------|----|
| Carton | 1 |
| Package | 32 |
| Weight Per each | 32 |