

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



AH460C12W Conn Pin&Sleeve 60A 125/250V 3P4W WT or Eaton Wiring Devices

Catalog Number	AH460C12W
Manufacturer	Eaton Wiring Devices
Description	Eaton Arrow Hart Pin and Sleeve Connector, IP69K Rated, #8 - #2 Awg, #10 - #2 Awg (Ground), #12 - #16 Awg (Pilot), 60A,
	125/250V, Back Wire, Orange, Nickel Plated Brass, IP67, Nylon,
	3-Pole, 4-Wire, 0.66-1.5IN (1.68-3.81CM), Female, Nylon,
Weight per unit	
Product Category	Pin & Sleeve Devices
Features	
dimensions	11.5000 IN X 5.1250 IN X 5.1250 IN
Material	Nylon
media	Yes
Descriptions	
Description	CONN PIN&SLEEVE 60A 125/250V 3P4W WT OR
extra long description	EWD AH460C12W Conn Pin&Sleeve 60A 1
Features	Eaton's Arrow Hart full line of pin and sleeve devices offer sturdy
	nylon construction, rugged design with corrosion resistant
	components for lasting electrical performance, and watertight
	sealing that provides IP69K protection so you can feel confident
	in even the most severe washdown environments.
Long Description	Eaton Arrow Hart pin and sleeve connector, IP69K Rated, #8 - #2
	AWG, #10 - #2 AWG (Ground), #12 - #16 AWG (Pilot), 60A,
	125/250V, Back wire, Orange, Nickel plated brass, IP67, Nylon,
~	3-pole, 4-wire, 0.66-1.5in (1.68-3.81cm), Female, Nylon
Product Type	Conn Pin&Sleeve 60A 125/250V 3P4W WT or
Special Features	Watertight P&S connectors
Manufacturer Information	
Brand	Eaton
GTIN	00040893619781
	AH460C12W
UPC	040893619781
Taxonomies, Classifications, and (Categories
Category Description	Pin & Sleeve Devices
Туре	Pin and Sleeve connector
Packaging	
Carton	
Package	
Weight Per each	16



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards

Application standard

Ind Facilities & Factories - Facility: Power Distribution and Control cRUus