

# Specifications

Photo is representative

## Eaton AHAC-P-1500-DMV

Eaton ceiling sensor, Dual relay, 120 to 347 VAC, Maintained closure, White, 32 kHz, Incand, MLV, halo, 1500 sq ft, Occupancy 748820

### General specifications

<b>PRODUCT NAME</b>	Eaton ceiling sensor
<b>CATALOG NUMBER</b>	AHAC-P-1500-DMV
<b>UPC</b>	032664748820
<b>PRODUCT LENGTH/DEPTH</b>	4.5 in
<b>PRODUCT HEIGHT</b>	1.42 in
<b>PRODUCT WIDTH</b>	0.8 in
<b>PRODUCT WEIGHT</b>	1 lb
<b>CERTIFICATIONS</b>	NOM cULus Listed
<b>PRODUCT TYPE</b>	Ceiling sensor



Powering Business Worldwide

## Product specifications

<b>FREQUENCY RATING</b>	32 kHz
<b>SPECIAL FEATURES</b>	Dual relay
<b>TYPE</b>	Ceiling sensor
<b>VOLTAGE RATING</b>	120 to 347 Vac
<b>SENSOR TYPE</b>	Occupancy
<b>CLOSURE TYPE</b>	Maintained
<b>LOAD TYPE</b>	INC MLV HAL
<b>RANGE</b>	1500 sq ft
<b>COLOR</b>	White

## Resources

<b>BROCHURES</b>	<a href="#">Arrow Hart commercial lighting controls brochure</a> <a href="#">Commercial ceiling sensors sell sheet</a>
<b>SPECIFICATIONS AND DATASHEETS</b>	<a href="#">Eaton Specification Sheet - AHAC-P-1500-DMV</a> <a href="#">AHAC-P - MicroSet PIR low/line voltage ceiling sensor spec sheet</a>

**PROJECT NAME:**

**PROJECT NUMBER:**

**PREPARED BY:**

**DATE:**



**Eaton Corporation plc** Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.



# Specifications

Photo is representative

## Eaton AHAC-P-1500-DMV

Eaton ceiling sensor, Dual relay, 120 to 347 VAC, Maintained closure, White, 32 kHz, Incand, MLV, halo, 1500 sq ft, Occupancy 748820

### General specifications

<b>PRODUCT NAME</b>	Eaton ceiling sensor
<b>CATALOG NUMBER</b>	AHAC-P-1500-DMV
<b>UPC</b>	032664748820
<b>PRODUCT LENGTH/DEPTH</b>	4.5 in
<b>PRODUCT HEIGHT</b>	1.42 in
<b>PRODUCT WIDTH</b>	0.8 in
<b>PRODUCT WEIGHT</b>	1 lb
<b>CERTIFICATIONS</b>	NOM cULus Listed
<b>PRODUCT TYPE</b>	Ceiling sensor



Powering Business Worldwide

## Product specifications

<b>FREQUENCY RATING</b>	32 kHz
<b>SPECIAL FEATURES</b>	Dual relay
<b>TYPE</b>	Ceiling sensor
<b>VOLTAGE RATING</b>	120 to 347 Vac
<b>SENSOR TYPE</b>	Occupancy
<b>CLOSURE TYPE</b>	Maintained
<b>LOAD TYPE</b>	INC MLV HAL
<b>RANGE</b>	1500 sq ft
<b>COLOR</b>	White

## Resources

<b>BROCHURES</b>	<a href="#">Arrow Hart commercial lighting controls brochure</a> <a href="#">Commercial ceiling sensors sell sheet</a>
<b>SPECIFICATIONS AND DATASHEETS</b>	<a href="#">Eaton Specification Sheet - AHAC-P-1500-DMV</a> <a href="#">AHAC-P - MicroSet PIR low/line voltage ceiling sensor spec sheet</a>

**PROJECT NAME:**

**PROJECT NUMBER:**

**PREPARED BY:**

**DATE:**



**Eaton Corporation plc** Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

