

# Specifications



## Eaton AHDS30SSR

Eaton motor control disconnect X-switch, IP69K/IP66 Ingress Protection, #14-10 AWG, 30A, Mounting feet/DIN rail, flush or 1/4" spacing, 600V, NEMA 4X, 12, Enclosure: 316L SS, Washdown, Three-phase, Rotary, NSF certified for food processing

### General specifications

<b>PRODUCT NAME</b>	Eaton motor control disconnect X-switch
<b>CATALOG NUMBER</b>	AHDS30SSR
<b>UPC</b>	032664755309
<b>PRODUCT LENGTH/DEPTH</b>	6.5 in
<b>PRODUCT HEIGHT</b>	13 in
<b>PRODUCT WIDTH</b>	5.8 in
<b>PRODUCT WEIGHT</b>	4.45 lb
<b>CERTIFICATIONS</b>	NSF Listed
<b>PRODUCT TYPE</b>	Motor control disconnect X-switch



Powering Business Worldwide

## Product specifications

<b>USED WITH</b>	NSF certified for use in food processing areas
<b>NEMA RATING</b>	12 4X
<b>ENCLOSURE</b>	NEMA 4X NEMA 12
<b>SPECIAL FEATURES</b>	IP69K, IP66 Ingress Protection Ratings
<b>TYPE</b>	Motor control disconnect X-Switch
<b>AMPERAGE RATING</b>	30A
<b>VOLTAGE RATING</b>	600 V
<b>NUMBER OF POLES</b>	Three-pole
<b>PHASE</b>	Three-phase
<b>ENCLOSURE MATERIAL</b>	316L stainless steel
<b>APPLICATION</b>	Industrial
<b>DEVICE GRADE</b>	Industrial
<b>ENVIRONMENTAL CONDITIONS</b>	Complex Food processing Washdown
<b>SWITCH TYPE</b>	Rotary switch
<b>MOUNTING METHOD</b>	Mounting feet/DIN rail Flush or 1/4 in spacing
<b>ALLOWABLE WIRE SIZE</b>	#14-10 AWG
<b>TERMINATION STYLE</b>	Rotary switch
<b>BREATHING VENT OR DRAIN</b>	No drain
<b>COLOR</b>	Gray

**PROJECT NAME:**

**PROJECT NUMBER:**

**PREPARED BY:**

**DATE:**

## Resources

SPECIFICATIONS AND DATASHEETS

[Eaton Specification Sheet - AHDS30SSR](#)

[X-Switch motor controllers disconnect switches spec sheet](#)



**Eaton Corporation plc** Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.



# Specifications



## Eaton AHDS30SSR

Eaton motor control disconnect X-switch, IP69K/IP66 Ingress Protection, #14-10 AWG, 30A, Mounting feet/DIN rail, flush or 1/4" spacing, 600V, NEMA 4X, 12, Enclosure: 316L SS, Washdown, Three-phase, Rotary, NSF certified for food processing

### General specifications

<b>PRODUCT NAME</b>	Eaton motor control disconnect X-switch
<b>CATALOG NUMBER</b>	AHDS30SSR
<b>UPC</b>	032664755309
<b>PRODUCT LENGTH/DEPTH</b>	6.5 in
<b>PRODUCT HEIGHT</b>	13 in
<b>PRODUCT WIDTH</b>	5.8 in
<b>PRODUCT WEIGHT</b>	4.45 lb
<b>CERTIFICATIONS</b>	NSF Listed
<b>PRODUCT TYPE</b>	Motor control disconnect X-switch



Powering Business Worldwide

## Product specifications

<b>USED WITH</b>	NSF certified for use in food processing areas
<b>NEMA RATING</b>	12 4X
<b>ENCLOSURE</b>	NEMA 4X NEMA 12
<b>SPECIAL FEATURES</b>	IP69K, IP66 Ingress Protection Ratings
<b>TYPE</b>	Motor control disconnect X-Switch
<b>AMPERAGE RATING</b>	30A
<b>VOLTAGE RATING</b>	600 V
<b>NUMBER OF POLES</b>	Three-pole
<b>PHASE</b>	Three-phase
<b>ENCLOSURE MATERIAL</b>	316L stainless steel
<b>APPLICATION</b>	Industrial
<b>DEVICE GRADE</b>	Industrial
<b>ENVIRONMENTAL CONDITIONS</b>	Complex Food processing Washdown
<b>SWITCH TYPE</b>	Rotary switch
<b>MOUNTING METHOD</b>	Mounting feet/DIN rail Flush or 1/4 in spacing
<b>ALLOWABLE WIRE SIZE</b>	#14-10 AWG
<b>TERMINATION STYLE</b>	Rotary switch
<b>BREATHING VENT OR DRAIN</b>	No drain
<b>COLOR</b>	Gray

**PROJECT NAME:**

**PROJECT NUMBER:**

**PREPARED BY:**

**DATE:**

## Resources

SPECIFICATIONS AND DATASHEETS

[Eaton Specification Sheet - AHDS30SSR](#)

[X-Switch motor controllers disconnect switches spec sheet](#)



**Eaton Corporation plc** Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

