


90° Angle Fittings

B420-378

One Hole Corner Angle


- Standard finishes: ZN, GRN
- Wt./C 60 Lbs. (27.2 kg)



B420-578

One Hole Corner Angle


- Standard finishes: ZN, GRN
- Wt./C 85 Lbs. (38.5 kg)



B420-778

One Hole Corner Angle


- Standard finishes: ZN, GRN
- Wt./C 107 Lbs. (48.5 kg)



B420-978

One Hole Corner Angle

- Standard finishes: ZN, GRN
- Wt./C 129 Lbs. (58.5 kg)




B101

Two Hole Corner Angle

- Standard finishes: ZN, GRN, HDG, SS4, AL
- Wt./C 37 Lbs. (16.8 kg)

PA ZN GRN




B230

Two Hole Corner Angle

- Standard finishes: ZN, GRN, HDG, SS4, AL
- Wt./C 37 Lbs. (16.8 kg)

PA ZN GRN




B231

Two Hole "No-Twist" Corner Angle

- Standard finishes: ZN, GRN, HDG
- Wt./C 41 Lbs. (18.6 kg)


PA ZN GRN



B359

Two Hole Corner Angle


- Standard finishes: ZN, GRN
- Wt./C 48 Lbs. (21.8 kg)



B360

Two Hole Corner Angle

- Standard finishes: ZN, GRN
- Wt./C 53 Lbs. (24.0 kg)



PA Pre-assembled fitting




4Dimension compatible fitting

Reference page 73 for general fitting and standard finish specifications.

B361

Two Hole Corner Angle

- Standard finishes: ZN, GRN
- Wt./C 60 Lbs. (27.2 kg)




B102

Three Hole Corner Angle

- Standard finishes: ZN, GRN, HDG, SS4
- Wt./C 56 Lbs. (25.4 kg)

PA ZN
GRN




B103

Three Hole Corner Angle

- Standard finishes: ZN, GRN, HDG, SS4
- Wt./C 56 Lbs. (25.4 kg)

PA ZN
GRN




B232

Three Hole Corner Angle

- Standard finishes: ZN, GRN, HDG, SS4
- Wt./C 56 Lbs. (25.4 kg)

PA ZN
GRN




B374

Three Hole Corner Angle

- Standard finishes: ZN, GRN, HDG
- Wt./C 56 Lbs. (25.4 kg)


PA ZN
GRN



B529

Three Hole Corner Angle

- Standard finishes: ZN, GRN
- Wt./C 78 Lbs. (35.4 kg)




B104

Four Hole Corner Angle

- Standard finishes: ZN, GRN, HDG, SS4, SS6, AL
- Wt./C 78 Lbs. (35.4 kg)

PA ZN
GRN




B115

Four Hole Corner Angle

- Standard finishes: ZN, GRN, HDG, SS4, AL
- Wt./C 76 Lbs. (34.5 kg)


PA ZN
GRN



B558

Four Hole Corner Angle

- Standard finishes: ZN, GRN
- Wt./C 73 Lbs. (33.1 kg)



PA Pre-assembled fitting



4Dimension compatible fitting


Reference page 73 for general fitting and standard finish specifications.

90° Angle Fittings

B235R

Three Hole (Right Hand) Offset Bent Angle


- 15/8" (41.3) from center to center of the holes that are shown with bolt heads
- Standard finishes: ZN, GRN
- Wt./C 53 Lbs. (24.0 kg)



B235L

Three Hole (Left Hand) Offset Bent Angle


- 15/8" (41.3) from center to center of the holes that are shown with bolt heads
- Standard finishes: ZN, GRN
- Wt./C 53 Lbs. (24.0 kg)



B236R

Three Hole (Right Hand) Offset Bent Angle


- Standard finishes: ZN, GRN
- Wt./C 65 Lbs. (29.5 kg)



B236L

Three Hole (Left Hand) Offset Bent Angle


- Standard finishes: ZN, GRN
- Wt./C 65 Lbs. (29.5 kg)



B237

Three Hole Offset Bent Tee


- Standard finishes: ZN, GRN
- Wt./C 71 Lbs. (32.2 kg)



B357

Four Hole Offset Bent Tee


- Standard finishes: ZN, GRN
- Wt./C 77 Lbs. (34.9 kg)



B238R

Four Hole (Right Hand) Offset Bent Tee


- Standard finishes: ZN, GRN
- Wt./C 76 Lbs. (34.5 kg)



B238L

Four Hole (Left Hand) Offset Bent Tee


- Standard finishes: ZN, GRN
- Wt./C 76 Lbs. (34.5 kg)



B239

Five Hole Offset Bent Tee


- Standard finishes: ZN, GRN
- Wt./C 96 Lbs. (43.5 kg)



B844

Universal Shelf Bracket


- Standard finishes: ZN, GRN, HDG, SS4
- Wt./C 132 Lbs. (59.9 kg)



B844W

Universal Shelf Bracket - Welded


- Standard finishes: ZN, GRN
- Wt./C 134 Lbs. (60.8 kg)



B888W

Universal Shelf Bracket - Welded


- Standard finishes: ZN, GRN
- Wt./C 197 Lbs. (89.4 kg)



B234R

Four Hole (Right Hand) Corner Gusset


- Standard finishes: ZN, GRN, HDG
- Wt./C 100 Lbs. (45.3 kg)



B234L

Four Hole (Left Hand) Corner Gusset


- Standard finishes: ZN, GRN, HDG
- Wt./C 100 Lbs. (45.3 kg)



B134R

Four Hole (Right Hand) Corner Gusset


- Standard finishes: ZN, GRN
- Wt./C 100 Lbs. (45.3 kg)



B134L

Four Hole (Left Hand) Corner Gusset


- Standard finishes: ZN, GRN
- Wt./C 100 Lbs. (45.3 kg)



B125

Three Hole Gussetted Shelf Angle


- Standard finishes: ZN, GRN
- Wt./C 67 Lbs. (30.4 kg)



B118

Four Hole Gussetted Shelf Angle

- Standard finishes: ZN, GRN, HDG
- Wt./C 102 Lbs. (46.2 kg)



4Dimension compatible fitting


Reference page 73 for general fitting and standard finish specifications.

90° Angle Fittings

B485

Four Hole Gussetted Shelf Angle


- Standard finishes: ZN, GRN
- Wt./C 148 Lbs. (67.1 kg)



B533

Five Hole Gussetted Shelf Angle


- Standard finishes: ZN, GRN
- Wt./C 141 Lbs. (63.9 kg)



B126

Four Hole Gussetted Three Way Shelf Angle


- Standard finishes: ZN, GRN
- Wt./C 101 Lbs. (45.8 kg)



B127

Five Hole Gussetted Three Way Shelf Angle


- Standard finishes: ZN, GRN
- Wt./C 135 Lbs. (61.2 kg)



B503R

Six Hole (Right Hand) Gussetted Corner Connection


- Standard finishes: ZN, GRN
- Wt./C 229 Lbs. (103.9 kg)



B503L

Six Hole (Left Hand) Gussetted Corner Connection


- Standard finishes: ZN, GRN
- Wt./C 229 Lbs. (103.9 kg)



B663

Seven Hole Gussetted Corner Connection


- Standard finishes: ZN, GRN
- Wt./C 289 Lbs. (131.1 kg)



B371

Two Hole Adjustable Corner Angle


- Standard finishes: ZN, GRN
- Wt./C 41 Lbs. (18.6 kg)



B372

Two Hole Adjustable Corner Angle

- Standard finishes: ZN, GRN
- Wt./C 38 Lbs. (17.2 kg)




 4Dimension compatible fitting

Reference page 73 for general fitting and standard finish specifications.


B496 Two Hole Adjustable Corner Angle

- Standard finishes: ZN, GRN
- Wt./C 85 Lbs. (38.5 kg)




B496-1 Two Hole Adjustable Corner Angle

- Standard finishes: ZN, GRN, HDG
- Wt./C 58 Lbs. (26.3 kg)




B371-2 Three Hole Adjustable Corner Angle

- Standard finishes: ZN, GRN
- Wt./C 61 Lbs. (27.6 kg)




B104SH Three Hole Adjustable Corner Angle

- Standard finishes: ZN, GRN
- Wt./C 68 Lbs. (30.8 kg)




B461 Two Hole Adjustable Corner Angle

- Standard finishes: ZN, GRN
- Wt./C 87 Lbs. (39.4 kg)




B112 Four Hole Adjustable Corner Angle

- Standard finishes: ZN, GRN
- Wt./C 180 Lbs. (81.6 kg)




B113 Four Hole Adjustable Corner Angle

- Standard finishes: ZN, GRN
- Wt./C 256 Lbs. (116.1 kg)




B109S Two Hole Tapped Corner Angle

- Standard finishes: ZN, GRN
- Wt./C 33 Lbs. (14.9 kg)



B521 Two Hole Bus Duct Angle

- Standard finishes: ZN, GRN
- Wt./C 37 Lbs. (16.8 kg)




Reference page 73 for general fitting and standard finish specifications.

90° Angle Fittings

B420-378

One Hole Corner Angle


- Standard finishes: ZN, GRN
- Wt./C 60 Lbs. (27.2 kg)



B420-578

One Hole Corner Angle


- Standard finishes: ZN, GRN
- Wt./C 85 Lbs. (38.5 kg)



B420-778

One Hole Corner Angle


- Standard finishes: ZN, GRN
- Wt./C 107 Lbs. (48.5 kg)



B420-978

One Hole Corner Angle

- Standard finishes: ZN, GRN
- Wt./C 129 Lbs. (58.5 kg)




B101

Two Hole Corner Angle

- Standard finishes: ZN, GRN, HDG, SS4, AL
- Wt./C 37 Lbs. (16.8 kg)

PA ZN GRN




B230

Two Hole Corner Angle

- Standard finishes: ZN, GRN, HDG, SS4, AL
- Wt./C 37 Lbs. (16.8 kg)

PA ZN GRN




B231

Two Hole "No-Twist" Corner Angle

- Standard finishes: ZN, GRN, HDG
- Wt./C 41 Lbs. (18.6 kg)


PA ZN GRN



B359

Two Hole Corner Angle


- Standard finishes: ZN, GRN
- Wt./C 48 Lbs. (21.8 kg)



B360

Two Hole Corner Angle

- Standard finishes: ZN, GRN
- Wt./C 53 Lbs. (24.0 kg)



PA Pre-assembled fitting



4Dimension compatible fitting


Reference page 73 for general fitting and standard finish specifications.

90° Angle Fittings

B361

Two Hole Corner Angle

- Standard finishes: ZN, GRN
- Wt./C 60 Lbs. (27.2 kg)




B102

Three Hole Corner Angle

- Standard finishes: ZN, GRN, HDG, SS4
- Wt./C 56 Lbs. (25.4 kg)

PA ZN
GRN




B103

Three Hole Corner Angle

- Standard finishes: ZN, GRN, HDG, SS4
- Wt./C 56 Lbs. (25.4 kg)

PA ZN
GRN




B232

Three Hole Corner Angle

- Standard finishes: ZN, GRN, HDG, SS4
- Wt./C 56 Lbs. (25.4 kg)

PA ZN
GRN




B374

Three Hole Corner Angle

- Standard finishes: ZN, GRN, HDG
- Wt./C 56 Lbs. (25.4 kg)


PA ZN
GRN



B529

Three Hole Corner Angle

- Standard finishes: ZN, GRN
- Wt./C 78 Lbs. (35.4 kg)




B104

Four Hole Corner Angle

- Standard finishes: ZN, GRN, HDG, SS4, SS6, AL
- Wt./C 78 Lbs. (35.4 kg)

PA ZN
GRN




B115

Four Hole Corner Angle

- Standard finishes: ZN, GRN, HDG, SS4, AL
- Wt./C 76 Lbs. (34.5 kg)


PA ZN
GRN



B558

Four Hole Corner Angle

- Standard finishes: ZN, GRN
- Wt./C 73 Lbs. (33.1 kg)



PA Pre-assembled fitting



Dimension compatible fitting


Reference page 73 for general fitting and standard finish specifications.

90° Angle Fittings

B235R

Three Hole (Right Hand) Offset Bent Angle


- 15/8" (41.3) from center to center of the holes that are shown with bolt heads
- Standard finishes: ZN, GRN
- Wt./C 53 Lbs. (24.0 kg)



B235L

Three Hole (Left Hand) Offset Bent Angle


- 15/8" (41.3) from center to center of the holes that are shown with bolt heads
- Standard finishes: ZN, GRN
- Wt./C 53 Lbs. (24.0 kg)



B236R

Three Hole (Right Hand) Offset Bent Angle


- Standard finishes: ZN, GRN
- Wt./C 65 Lbs. (29.5 kg)



B236L

Three Hole (Left Hand) Offset Bent Angle


- Standard finishes: ZN, GRN
- Wt./C 65 Lbs. (29.5 kg)



B237

Three Hole Offset Bent Tee


- Standard finishes: ZN, GRN
- Wt./C 71 Lbs. (32.2 kg)



B357

Four Hole Offset Bent Tee


- Standard finishes: ZN, GRN
- Wt./C 77 Lbs. (34.9 kg)



B238R

Four Hole (Right Hand) Offset Bent Tee


- Standard finishes: ZN, GRN
- Wt./C 76 Lbs. (34.5 kg)



B238L

Four Hole (Left Hand) Offset Bent Tee


- Standard finishes: ZN, GRN
- Wt./C 76 Lbs. (34.5 kg)



B239

Five Hole Offset Bent Tee


- Standard finishes: ZN, GRN
- Wt./C 96 Lbs. (43.5 kg)



B844

Universal Shelf Bracket


- Standard finishes: ZN, GRN, HDG, SS4
- Wt./C 132 Lbs. (59.9 kg)



B844W

Universal Shelf Bracket - Welded


- Standard finishes: ZN, GRN
- Wt./C 134 Lbs. (60.8 kg)



B888W

Universal Shelf Bracket - Welded


- Standard finishes: ZN, GRN
- Wt./C 197 Lbs. (89.4 kg)



B234R

Four Hole (Right Hand) Corner Gusset


- Standard finishes: ZN, GRN, HDG
- Wt./C 100 Lbs. (45.3 kg)



B234L

Four Hole (Left Hand) Corner Gusset


- Standard finishes: ZN, GRN, HDG
- Wt./C 100 Lbs. (45.3 kg)



B134R

Four Hole (Right Hand) Corner Gusset


- Standard finishes: ZN, GRN
- Wt./C 100 Lbs. (45.3 kg)



B134L

Four Hole (Left Hand) Corner Gusset


- Standard finishes: ZN, GRN
- Wt./C 100 Lbs. (45.3 kg)



B125

Three Hole Gussetted Shelf Angle


- Standard finishes: ZN, GRN
- Wt./C 67 Lbs. (30.4 kg)



B118

Four Hole Gussetted Shelf Angle

- Standard finishes: ZN, GRN, HDG
- Wt./C 102 Lbs. (46.2 kg)



4Dimension compatible fitting


Reference page 73 for general fitting and standard finish specifications.

90° Angle Fittings

B485

Four Hole Gussetted Shelf Angle


- Standard finishes: ZN, GRN
- Wt./C 148 Lbs. (67.1 kg)



B533

Five Hole Gussetted Shelf Angle


- Standard finishes: ZN, GRN
- Wt./C 141 Lbs. (63.9 kg)



B126

Four Hole Gussetted Three Way Shelf Angle


- Standard finishes: ZN, GRN
- Wt./C 101 Lbs. (45.8 kg)



B127

Five Hole Gussetted Three Way Shelf Angle


- Standard finishes: ZN, GRN
- Wt./C 135 Lbs. (61.2 kg)



B503R

Six Hole (Right Hand) Gussetted Corner Connection


- Standard finishes: ZN, GRN
- Wt./C 229 Lbs. (103.9 kg)



B503L

Six Hole (Left Hand) Gussetted Corner Connection


- Standard finishes: ZN, GRN
- Wt./C 229 Lbs. (103.9 kg)



B663

Seven Hole Gussetted Corner Connection


- Standard finishes: ZN, GRN
- Wt./C 289 Lbs. (131.1 kg)



B371

Two Hole Adjustable Corner Angle


- Standard finishes: ZN, GRN
- Wt./C 41 Lbs. (18.6 kg)



B372

Two Hole Adjustable Corner Angle

- Standard finishes: ZN, GRN
- Wt./C 38 Lbs. (17.2 kg)




 4Dimension compatible fitting

Reference page 73 for general fitting and standard finish specifications.


B496 Two Hole Adjustable Corner Angle

- Standard finishes: ZN, GRN
- Wt./C 85 Lbs. (38.5 kg)




B496-1 Two Hole Adjustable Corner Angle

- Standard finishes: ZN, GRN, HDG
- Wt./C 58 Lbs. (26.3 kg)




B371-2 Three Hole Adjustable Corner Angle

- Standard finishes: ZN, GRN
- Wt./C 61 Lbs. (27.6 kg)




B104SH Three Hole Adjustable Corner Angle

- Standard finishes: ZN, GRN
- Wt./C 68 Lbs. (30.8 kg)




B461 Two Hole Adjustable Corner Angle

- Standard finishes: ZN, GRN
- Wt./C 87 Lbs. (39.4 kg)




B112 Four Hole Adjustable Corner Angle

- Standard finishes: ZN, GRN
- Wt./C 180 Lbs. (81.6 kg)




B113 Four Hole Adjustable Corner Angle

- Standard finishes: ZN, GRN
- Wt./C 256 Lbs. (116.1 kg)




B109S Two Hole Tapped Corner Angle

- Standard finishes: ZN, GRN
- Wt./C 33 Lbs. (14.9 kg)



B521 Two Hole Bus Duct Angle

- Standard finishes: ZN, GRN
- Wt./C 37 Lbs. (16.8 kg)



Reference page 73 for general fitting and standard finish specifications.