

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



B41 B-Cap Wire Connector, Model B4 Blue/Gray, 25/Box Ideal

Catalog Number	B41
Manufacturer	ldeal
Description	Color: Blue/Gray, Buchanan, Wire Connector, B-Cap®, Conductor Range: 14 - 6 Awg, 2/12 Awg Min, 2/6 Awg Max, Number Of Conductors: 2 to 6, Material: Flame-Retardant Polypropelene, Voltage Rating: 600 V, Environmental Conditions: Tough, UI 94V-2 Flame-Retardant Shell Rated At 105 Deg C (221 F), Model Number: B4
Weight per unit	0.0180 (lbs/each)
Product Category	Electrical Fixture Conn (Nuts
Features	
Material	Flame-retardant Polypropelene
Voltage Rating	600
Material, Color, and Finish	
Color	Blue/Gray
Descriptions	
Description extra long description	B-CAP WIRE CONNECTOR, MODEL B4 BLUE/GRAY, 25/BOX IDEAL B4-1 B-CAP B4 BLUE GRAY, 25 B
Features	The B-CAP Wire Connector gets you in those hard-to reach spots comfortably, especially when you're retrofitting or updating. Slim, classic fins and an expanding interior spring give the B-CAP a secure grip with extra leverage, making it the most compact connector on the market for up to 5 #12 (Red Model B2). The unique, space-saving profile of the B-CAP makes it perfect for retrofit work and shallow boxes. The B-CAP also features a tough, flame-retardant shell that withstands environmental extremes with a de
Long Description	Color: Blue/Gray, Buchanan, Wire Connector, B-CAP®, Conductor Range: 14 - 6 AWG, 2/12 AWG Min, 2/6 AWG Max, Number Of Conductors: 2 to 6, Material: Flame-retardant Polypropelene, Voltage Rating: 600 V, Environmental Conditions: Tough, UL 94V-2 Flame-Retardant Shell Rated At 105 DEG C (221 F), Model Number: B4
Manufacturer Information	
Brand	Buchanan
GTIN	00781789452036
UPC	781789452036



standard

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

gories
Datacom Wiring Devices and Accessories
25
Inactive
250
0.018
Insulating or Joining 1 or more conductors
Tough, UL 94V-2 Flame-Retardant Shell Rated At 105 DEG C (221 F)

CSA C22.2 #188, UL 486C Listed, RoHS