

Specifications



Eaton BR2040L200R

Eaton Eaton BR main lug loadcenter, No feed-thru lugs, includes BREQS125 hold-down screw, 200 A, C3R, Aluminum, NEMA 3R, Metallic, 25 kAIC, BWH, 40 Circuits, Twenty-four pole, 20 Spaces, Three-wire, Single-phase, 120/240V, #1 AWG-300 kcmil Cu/Al

General specifications

| | |
|-----------------------------|---------------------------------------|
| PRODUCT NAME | Eaton BR main lug loadcenter |
| CATALOG NUMBER | BR2040L200R |
| UPC | 786676447553 |
| PRODUCT LENGTH/DEPTH | 5.19 in |
| PRODUCT HEIGHT | 25 in |
| PRODUCT WIDTH | 14.31 in |
| PRODUCT WEIGHT | 15.5 lb |
| WARRANTY | 10 year |
| CERTIFICATIONS | UL 50 UL 67 |
| CATALOG NOTES | Has notch for brhdk125 hold-down kit. |



Powering Business Worldwide

Product specifications

| | |
|-----------------------------|--|
| SPECIAL FEATURES | No feed-thru lugs, includes BREQS125 hold-down screw |
| TYPE | Main lug |
| AMPERAGE RATING | 200 A |
| BUS MATERIAL | Aluminum |
| COVER | Cover included |
| MAIN CIRCUIT BREAKER | BWH |
| NUMBER OF CIRCUITS | 40 |
| NUMBER OF SPACES | 20 |
| PHASE | Single-phase |
| USED WITH | Type BR 1-inch breakers |
| VOLTAGE RATING | 120/240V |
| WIRE SIZE | #1 AWG-300 kcmil Cu/Al |
| BOX SIZE | C3R |
| ENCLOSURE | NEMA 1 |
| ENCLOSURE MATERIAL | Metallic |
| INTERRUPT RATING | 25 kAIC |
| NUMBER OF WIRES | 3 |

Resources

| | |
|-------------------------------|--|
| CATALOGS | Residential and Light Commercial, Loadcenters and Circuit Breakers, Volume 1 Tab 1 |
| SPECIFICATIONS AND DATASHEETS | Eaton Specification Sheet - BR2040L200R |
| WARRANTY GUIDES | Eaton type BR circuit breaker limited warranty June 2024 |

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.