

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



GTIN

UPC

BR2424L125 24/24C 125A 1PH Mlo Loadcenter Eaton Corp

Eaton Corp	
Catalog Number	BR2424L125
Manufacturer	Eaton Corp
Description	Main Lug Load Center, 24 Spaces, 24 Circuits, 125 A, 120/240 V Ac, #6 to 2/0 Awg Wire Size, Metallic Material, Aluminum Bus Material, 14.31 In Overall Length, 3.88 In Overall Width, 23 In Overall Height
Weight per unit	24.0 (lbs/each)
Product Category	Single Phase Main Lug Load Cen
eatures	
amperage rating	125 VAC
Box Size	QUARTZ LIGHTING LENS, GLASS LENS REFRACTOR/LENS TYPE; QF500F QUARTZ FLOODLIGHT FIXTURE TYPE; RAB[R] BRAND
cover	Cover included
Cover Type	Cover included
dimensions	98.5520millimetreX36.3474centimetreX58.4200centimetre
Number of Wires	Three-wire
Phase	1 PH
used with	Type BR 1-inch breakers
Material, Color, and Finish	
Enclosure Material	Metallic
Dimensions and Weight	
Size	C2
Descriptions	
Also Known As	panelboard
	panel
	panel board
	breaker box
	load center
	breaker panel
	Fuse box
	electric panel
Description	24/24C 125A 1PH MLO LOADCENTER
extra long description	ETN BR2424L125 BR style 1-inch load
Manufacturer Information	

00786676447102

786676447102



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies	Classifications,	and Categories
-------------------	------------------	----------------

Category Description	LOADCENTERS & COVERS
igcc	PLUG, NON POLARIZED TYPE; THERMOPLASTIC MATERIAL;
	WHITE COLOR; 1-15P CONFIGURATION; UL 1706, CSA APPROVAL;
	125 V VOLTAGE RATING; 15 AMPERE CURRENT RATING; IMPACT
	RESISTANT; (2) 18 AWG CORD SIZE; HOMESELECT[T] BRAND
Туре	MAIN LUG
unspsc code	39121101

Availability

Status Inactive

Packaging

Carton 1
Weight Per each 24

Uses, Certifications, and Standards

oo, oo tiiioatioiio, aiia o	21144140	
Enclosure	NEMA 1	
Mounting	Combination	
standard	UL 67;UL 50	