

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1701 North Jackson Suite E 78501-0000, TX McAllen Phone: 956-331-2410 Fax: 956-331-2411



BR250H Type BR 2P 50A 240V Eaton Corp

| Catalog Number | BR250H |
|---------------------------|--|
| Manufacturer | Eaton Corp |
| Description | Eaton BR Thermal Magnetic Circuit Breaker, Type BR 1-Inch Plug-On High-Magnetic Circuit Breaker, High-Magnetic, 50 A, 10 Kaic, Two-Pole, 240V, BR, Common Breaker Trip, #14-4 Awg Cu/Al, Q28, BR, Type BR Loadcenters |
| Weight per unit | |
| Product Category | 2P Special Application Plug-In |
| eatures | |
| dimensions | 3.0000 IN X 2.0000 IN X 3.0000 IN |
| interrupt rating | 10 |
| Poles | 2 |
| Voltage Rating | 240 V - 240 V |
| Descriptions | |
| Description | TYPE BR 2P 50A 240V |
| extra long description | ETN BR250H TYPE BR 2p 50a 240v |
| Features | Eaton's BR circuit breakers are used in indoor and outdoor BR loadcenters, spa panels, meter breakers and sub panels. They are designed for a wide range of applications such as high short-circuit interrupt, series rating combinations with upstream main breakers, thermal magnetic, AFCI, GFCI, equipment protection and dual function AF/GF. |
| Long Description | Eaton BR thermal magnetic circuit breaker, Type BR 1-Inch plug-on high-magnetic circuit breaker, High-magnetic, 50 A, 10 kAIC, Two-pole, 240V, BR, Common breaker trip, #14-4 AWG Cu/AI, Q28, BR, Type BR Loadcenters |
| Product Type | Type BR 2P 50A 240V |
| Special Features | High-Magnetic |
| Manufacturer Information | |
| Brand | Eaton |
| GTIN | 00786676374507 |
| Manufacturers Part Number | BR250H |
| UPC | 786676374507 |

Taxonomies, Classifications, and Categories

| Category Description | Loadcenter Plug In Breakers and Accessories |
|----------------------|---|
| Туре | Thermal magnetic circuit breakers |



standard

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1701 North Jackson Suite E 78501-0000, TX McAllen Phone: 956-331-2410 Fax: 956-331-2411

| Packaging | |
|-------------------------------------|--|
| Carton | 5 |
| Package | 25 |
| Weight Per each | 0.5 |
| Uses, Certifications, and Standards | |
| Application | Generation - Renewable Energy - Alternative EnergyGeneration - |
| | Conventional Energy - Conventional EnergyDatacenters - IT |
| | Space: CI and Hyper ConvergedMarine Vessels and Equipment - |
| | Marine Vessels and Equipment - OtherOther |

UL 489, Federal Specifications Classification W-C375