



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## BR260 Type BR BRKR 60A/2 Pole 120/240V 10K *Eaton Corp*

|                  |   |
|------------------|---|
| Catalog Number   | BR260   |
| Manufacturer     | Eaton Corp  |
| Description      | Standard Trip Circuit Breaker, 60 A, Common Tripping Mechanism, Line and Load Lug Terminal, Plug-On, 120/240 V Ac, 3 In Overall Height, 3 In Overall Length, 2 In Overall Width |
| Weight per unit  | 0.5000 (lbs/each)   |
| Product Category | 2 Pole Standard Trip Plug-In  |

### Features

|            |                                   |
|------------|-----------------------------------|
| dimensions | 1.9000 IN X 2.9000 IN X 2.5000 IN |
| Poles      | Two-pole                          |
| Trip Type  | Common breaker trip               |

### Descriptions

|                        |                                      |
|------------------------|--------------------------------------|
| Description            | TYPE BR BRKR 60A/2 POLE 120/240V 10K |
| extra long description | ETN BR260 Type BR Breaker 60A/2 Pol  |

### Manufacturer Information

|      |                |
|------|----------------|
| GTIN | 00786676363105 |
| UPC  | 786676363105   |

### Taxonomies, Classifications, and Categories

|                      |   |
|----------------------|---|
| Category Description | Loadcenter Plug In Breakers and Accessories |
| Type                 | Thermal magnetic circuit breakers           |

### Packaging

|                 |     |
|-----------------|-----|
| Carton          | 5   |
| Package         | 25  |
| Weight Per each | 0.5 |

### Uses, Certifications, and Standards

|             |  |
|-------------|--|
| Application | Marine Vessels and Equipment - Marine Vessels and Equipment - OtherOtherGeneration - Renewable Energy - Alternative EnergyGeneration - Conventional Energy - Conventional EnergyDatacenters - IT Space: Cl and Hyper Converged |
| standard    | UL 489,Federal Specifications Classification W-C375  |