

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



BT1MC 4" Nyln CBL Tie SS Barb Min Cross Sec WHT Panduit Corporation

Catalog Number	BT1MC
Manufacturer	Panduit Corporation
Description	The BT1M-C Dome-Top® Barb Ty, Features A Unique Patented
	Design With Its Round Smooth Edges. Paired With The
	Stainless-Steel Locking Barb, These Cable Ties Provide Consistent Performance, Reliability and Infinite Adjustability Through The
	Entire Bundle Range. Miniature Cross Section, 4.0" (102MM)
	Length. Appropriate For Indoor Use, Made Of Nylon 6.6, Are
	Natural In Color and Come In Packages Of 100.
Weight per unit	1.0 (lbs/each)
Product Category	Cable Ties & Wraps
Features	
media	Yes
Tensile Strength	18
Dimensions and Weight	
Length	4
Thickness	0.04
Descriptions	
Description	4" NYLN CBL TIE SS BARB MIN CROSS SEC WHT
extra long description	PAN BT1M-C Dome-Top® BT1M-C Barb Ti
Long Description	The BT1M-C Dome-Top® barb ty, features a unique patented
	design with its round smooth edges. Paired with the
	stainless-steel locking barb, these cable ties provide consistent
	performance, reliability and infinite adjustability through the
	entire bundle range. Miniature cross section, 4.0" (102mm)
	length. Appropriate for Indoor use, made of Nylon 6.6, are
Product Type	natural in color and come in packages of 100. Dome-Top® BT1M-C Barb Tie, PA6.6, 4"L, 18LB, PK100
Special Features	Indoor
Manufacturer Information	
Brand	PANDUIT
GTIN	00074983413027
Manufacturers Part Number	BT1M-C
UPC	074983413027
	7.77



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Cate	gories
Category Description	Screws, Bolts, Staples, Jack Chains, Washers & TY-Raps
Туре	Cable Tie
Availability minimum qty	100
Packaging	
Carton	100
Package	1000
Weight Per each	1
Uses, Certifications, and Standards	
standard	UL 62275 (File E56854), CSA-C22.2 No. 62275, 11130200, NRC

10CFR50, QPL-AS23190, CSA Certified, RoHS Compliant