



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2 Solar Circle
30265-0000, GA Newnan
Phone: 678-621-2507
Fax: 678-621-2508



BT4 1-1/4" BT MGL Conduit Body *Crouse-Hinds*

Catalog Number	BT4
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet B Mogul Conduit Body, Feraloy Iron Alloy, T Shape, 1-1/4"
Weight per unit	4.0 (lbs/each)
Product Category	Bodies & Covers

Features

dimensions	9.5600 IN X 2.3100 IN X 3.1600 IN
------------	-----------------------------------

Material, Color, and Finish

Finish	Electrogalvanized With Aluminum Acrylic Painted
--------	---

Dimensions and Weight

Height	2-5/16
Hub Size	1-1/4 in
Length	9-9/16
Width	3-5/32

Descriptions

Description	1-1/4" BT MGL CONDUIT BODY
extra long description	CRS-H BT4 1 1/4 NPT IRON T MOGUL
Features	Crouse-Hinds series mogul bodies are installed in conduit systems to act as pull outlets for conductors that are stiff due to large size or type of insulation. Mogul bodies provide longer openings needed when pulling large conductors and prevent sharp bends and kinks during installation. Mogul conduit bodies are manufactured in trade sizes 1/2" to 6" and are available in Feraloy iron alloy and copper-free aluminum. Our iron alloy bodies are available with a hot dip galvanized finish for added corrosion
Long Description	Eaton Crouse-Hinds series Condulet B mogul conduit body, Feraloy iron alloy, T shape, 1-1/4"
Product Type	1 1/4 NPT Iron T Mogul

Manufacturer Information

Brand	Eaton
GTIN	00782274746425
UPC	782274746425

Taxonomies, Classifications, and Categories

Category Description	Form 9 condulets, covers & gaskets
Type	Mogul conduit body



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2 Solar Circle
30265-0000, GA Newnan
Phone: 678-621-2507
Fax: 678-621-2508

Packaging

Carton	1
Package	2
Weight Per each	3.95

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
standard	UL 514B, CSA C22.2, FEDERAL SPECIFICATION W-C-586D