

# Specifications



Photo is representative



## Eaton C0150E5EFB

Eaton Type MTE industrial control transformer, pv: 200/220/440v, 208/230/460v, 240/480v, sv: 23/110v, 24/115v, 25/120v, 55°C, 150 va , cu magnet wire

### General specifications

|                      |                                                                                                                                                                                                                 |
|----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| PRODUCT NAME         | Eaton Type MTE industrial control transformer                                                                                                                                                                   |
| CATALOG NUMBER       | C0150E5EFB                                                                                                                                                                                                      |
| UPC                  | 786680421761                                                                                                                                                                                                    |
| PRODUCT LENGTH/DEPTH | 3.96 in                                                                                                                                                                                                         |
| PRODUCT HEIGHT       | 4.65 in                                                                                                                                                                                                         |
| PRODUCT WIDTH        | 3.75 in                                                                                                                                                                                                         |
| PRODUCT WEIGHT       | 8.5 lb                                                                                                                                                                                                          |
| WARRANTY             | Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.                                |
| COMPLIANCES          | RoHS Compliant                                                                                                                                                                                                  |
| CERTIFICATIONS       | UL Listed<br>cUL Certified<br>CSA Certified                                                                                                                                                                     |
| CATALOG NOTES        | Epoxy encapsulated, Laminations of high quality silicon steel to minimize core losses and optimize performance, 50/60Hz operation, 130°C insulation system standard, Molded-in terminals for maximum durability |

| Physical Attributes |                 |
|---------------------|-----------------|
| COIL MATERIAL       | Copper windings |
| DESIGN              | MTE             |
| TAP SIZE            | None            |

| Performance Ratings |                                            |
|---------------------|--------------------------------------------|
| PRIMARY VOLTAGE     | 200/220/440 V,<br>208/230/460 V, 240/480 V |
| TEMPERATURE RATING  | 55°C                                       |
| VOLT AMPERE RATING  | 150 VA                                     |
| SECONDARY VOLTAGE   | 23/110 V, 24/115 V, 25/120 V               |

| Miscellaneous    |                                                                          |
|------------------|--------------------------------------------------------------------------|
| MODIFICATION 1   | Factory-mounted two-pole primary fuse block for non-rejection type fuses |
| SPECIAL FEATURES | Primary fuse block                                                       |

| Resources                     |                                                        |
|-------------------------------|--------------------------------------------------------|
| SPECIFICATIONS AND DATASHEETS | <a href="#">Eaton Specification Sheet - C0150E5EFB</a> |

|                 |  |
|-----------------|--|
| PROJECT NAME:   |  |
| PROJECT NUMBER: |  |
| PREPARED BY:    |  |
| DATE:           |  |



**Eaton Corporation plc**  
 Eaton House  
 30 Pembroke Road  
 Dublin 4, Ireland  
 Eaton.com

Follow us on social media to get the latest product and support information.



# Specifications



Photo is representative



## Eaton C0150E5EFB

Eaton Type MTE industrial control transformer, pv: 200/220/440v, 208/230/460v, 240/480v, sv: 23/110v, 24/115v, 25/120v, 55°C, 150 va , cu magnet wire

### General specifications

|                      |                                                                                                                                                                                                                 |
|----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| PRODUCT NAME         | Eaton Type MTE industrial control transformer                                                                                                                                                                   |
| CATALOG NUMBER       | C0150E5EFB                                                                                                                                                                                                      |
| UPC                  | 786680421761                                                                                                                                                                                                    |
| PRODUCT LENGTH/DEPTH | 3.96 in                                                                                                                                                                                                         |
| PRODUCT HEIGHT       | 4.65 in                                                                                                                                                                                                         |
| PRODUCT WIDTH        | 3.75 in                                                                                                                                                                                                         |
| PRODUCT WEIGHT       | 8.5 lb                                                                                                                                                                                                          |
| WARRANTY             | Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.                                |
| COMPLIANCES          | RoHS Compliant                                                                                                                                                                                                  |
| CERTIFICATIONS       | UL Listed<br>cUL Certified<br>CSA Certified                                                                                                                                                                     |
| CATALOG NOTES        | Epoxy encapsulated, Laminations of high quality silicon steel to minimize core losses and optimize performance, 50/60Hz operation, 130°C insulation system standard, Molded-in terminals for maximum durability |

| Physical Attributes |                 |
|---------------------|-----------------|
| COIL MATERIAL       | Copper windings |
| DESIGN              | MTE             |
| TAP SIZE            | None            |

| Performance Ratings |                                            |
|---------------------|--------------------------------------------|
| PRIMARY VOLTAGE     | 200/220/440 V,<br>208/230/460 V, 240/480 V |
| TEMPERATURE RATING  | 55°C                                       |
| VOLT AMPERE RATING  | 150 VA                                     |
| SECONDARY VOLTAGE   | 23/110 V, 24/115 V, 25/120 V               |

| Miscellaneous    |                                                                          |
|------------------|--------------------------------------------------------------------------|
| MODIFICATION 1   | Factory-mounted two-pole primary fuse block for non-rejection type fuses |
| SPECIAL FEATURES | Primary fuse block                                                       |

| Resources                     |                                                        |
|-------------------------------|--------------------------------------------------------|
| SPECIFICATIONS AND DATASHEETS | <a href="#">Eaton Specification Sheet - C0150E5EFB</a> |

|                 |  |
|-----------------|--|
| PROJECT NAME:   |  |
| PROJECT NUMBER: |  |
| PREPARED BY:    |  |
| DATE:           |  |



**Eaton Corporation plc**  
 Eaton House  
 30 Pembroke Road  
 Dublin 4, Ireland  
 Eaton.com

Follow us on social media to get the latest product and support information.

