Specifications



Photo is representative





Eaton C0500E1B

Eaton Type MTE industrial control transformer, pv: 120 x 240v, taps: none

General specifications	
PRODUCT NAME	Eaton Type MTE industrial control transformer
CATALOG NUMBER	C0500E1B
UPC	786680423086
PRODUCT LENGTH/DEPTH	6.11 in
PRODUCT HEIGHT	5.14 in
PRODUCT WIDTH	5.25 in
PRODUCT WEIGHT	17.4 lb
WARRANTY	Eaton Selling Policy 25- 000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
COMPLIANCES	RoHS Compliant
CERTIFICATIONS	UL Listed CSA Certified cUL Certified
CATALOG NOTES	Epoxy encapsulated, Laminations of high quality silicon steel to minimize core losses and optimize performance, 50/60Hz operation, 130°C insulation system standard, Molded-in terminals for maximum durability



Physical Attributes	
COIL MATERIAL	Copper windings
DESIGN	MTE
TAP SIZE	None

Performance Ratings	
PRIMARY VOLTAGE	120 x 240 V
TEMPERATURE RATING	55°C
VOLT AMPERE RATING	500 VA
SECONDARY VOLTAGE 24 V	

Resources	
SPECIFICATIONS AND DATASHEETS	<u>Eaton Specification Sheet -</u> <u>C0500E1B</u>

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

 $\hbox{@ 2025 Eaton.}$ All Rights Reserved.

Follow us on social media to get the latest product and support information.











Specifications



Photo is representative





Eaton C0500E1B

Eaton Type MTE industrial control transformer, pv: 120 x 240v, taps: none

General specifications	
PRODUCT NAME	Eaton Type MTE industrial control transformer
CATALOG NUMBER	C0500E1B
UPC	786680423086
PRODUCT LENGTH/DEPTH	6.11 in
PRODUCT HEIGHT	5.14 in
PRODUCT WIDTH	5.25 in
PRODUCT WEIGHT	17.4 lb
WARRANTY	Eaton Selling Policy 25- 000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
COMPLIANCES	RoHS Compliant
CERTIFICATIONS	UL Listed CSA Certified cUL Certified
CATALOG NOTES	Epoxy encapsulated, Laminations of high quality silicon steel to minimize core losses and optimize performance, 50/60Hz operation, 130°C insulation system standard, Molded-in terminals for maximum durability



Physical Attributes	
COIL MATERIAL	Copper windings
DESIGN	MTE
TAP SIZE	None

Performance Ratings	
PRIMARY VOLTAGE	120 x 240 V
TEMPERATURE RATING	55°C
VOLT AMPERE RATING	500 VA
SECONDARY VOLTAGE 24 V	

Resources	
SPECIFICATIONS AND DATASHEETS	<u>Eaton Specification Sheet -</u> <u>C0500E1B</u>

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

 $\hbox{@ 2025 Eaton.}$ All Rights Reserved.

Follow us on social media to get the latest product and support information.









