




ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

3205 Axtell
88101-0000, NM Clovis
Phone: 575-742-2504
Fax: 575-742-2508



C1LG6 1" Wiring Duct Cover, Light Gray *Panduit Corporation*

Catalog Number	C1LG6
Manufacturer	Panduit Corporation
Description	The C1LG6 PVC Flush Wiring Duct Cover Features A Non-Slip, Liner to Prevent Cover Slide. Designed With The User In Mind, The Cover Is Easy to Install and Remove. The General-Purpose Lead-Free PVC Material Is Suitable For Use In Indoor Applications. UI 94 Flame Class Of V-0 With A UI Recognized Continuous-Use Temperature Up to 122°F (50°C). 0.35" X 1.25" (8.9 MM X 31.8 MM) and 6' (1.83 M) Long. Color Light Gray.
Weight per unit	0.0670 (lbs/each)
Product Category	Wiring Duct & Accessories

Features

connection	Snap-on
media	Yes

Material, Color, and Finish

Color	Gray
-------	------

Dimensions and Weight

Length	NA
Width	1.25

Descriptions

Description	1" WIRING DUCT COVER, LIGHT GRAY
extra long description	PAN C1LG6 Panduct® C1LG6 Flush Duct
Long Description	The C1LG6 PVC Flush Wiring Duct Cover features a non-slip, liner to prevent cover slide. Designed with the user in mind, the cover is easy to install and remove. The general-purpose lead-free PVC material is suitable for use in indoor applications. UL 94 flame class of V-0 with a UL recognized continuous-use temperature up to 122°F (50°C). 0.35" x 1.25" (8.9 mm x 31.8 mm) and 6' (1.83 m) long. Color Light Gray.
Product Type	Panduct® C1LG6 Flush Duct Cover

Manufacturer Information

Brand	PANDUIT
GTIN	00074983230402
Manufacturers Part Number	C1LG6
UPC	074983230402



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

3205 Axtell
88101-0000, NM Clovis
Phone: 575-742-2504
Fax: 575-742-2508

Taxonomies, Classifications, and Categories

Category Description WIRE DUCT AND COVERS
Type Flushed Duct Cover

Availability

minimum qty 6

Packaging

Carton 6

Package 120

Weight Per foot 0.067

Uses, Certifications, and Standards

Application Cover for Wiring Duct

standard CE Compliant;CSA Certified;Flammability Ratings: UL94 V-0;RoHS
Compliant;UL Recognized