

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

3705 Lee Street 71302-0000, LA Alexandria Phone: 318-445-1336 Fax: 318-445-8356

1	Ē	
	ī	1
 and a	ŧ.	

C25DND330B Open N-R 3P 30A DP Cont SCR/PP W/QC Term 240VAC CO Eaton Corp

Catalog Number	C25DND330B	
Manufacturer	Eaton Corp	
Description	Definite Purpose Control - Contactor, 3 Poles, 30 A, 208 to 240 V	
	Ac, 40 A Resistive Load, 1/3 Phases, 5 HP (Single Phase);10 HP	
	(Three Phase);3.7 KW (Single Phase);7.5 KW (Three Phase) Motor	
	Power, 15 to 50 A Frame, Quick Connect Terminal Connection,	
	-13 °F Operating Temperature, +158 °F Operating Temperature,	
	Din Rail Mount, 50 to 60 HZ, 3.75 In Overall Height, 3.35 In Overall Length, 2.40 In Overall Width, 1.19 LB	
Weight per unit		
Product Category	1.2 (lbs/each) Definite Purpose Contactors	
Features	Demine ruipose contactors	
Enclosure Type	Open with metal mounting plate	
induct amp/res amp rating	30/40	
Voltage Rating	240	
Dimensions and Weight		
Depth	3.35	
Height	2.5	
Width	2.4	
Descriptions		
Description	OPEN N-R 3P 30A DP CONT SCR/PP W/QC TERM 240VAC CO	
extra long description	ETN C25DND330B OP N-R 3P 30ADPCNT S	
Manufacturer Information		
Brand	EATON CUTLER-HAMMER	
GTIN	00782116300617	
UPC	782116300617	
Taxonomies, Classifications, and Cate	gories	
Category Description	DP CONTACTORS	
Туре	Definite purpose contactor	
Packaging		
Carton		
Weight Per each	1.19	
Uses, Certifications, and Standards		
standard	UL Recognized, CSA Certified, RoHS Compliant	