

# Specifications



Photo is representative



## Eaton C25DNF330C

Eaton definite purpose contactor, Quick, 30A, 208-240 Vac at 50/60 Hz, Open with metal mounting plate, 15-50A, two- or 3P, 15-50A, two- and 3P, Contactor, 3P, Global ratings, Box lugs (posidrive setscrew) and quick connect terminals

### General specifications

<b>PRODUCT NAME</b>	Eaton definite purpose contactor
<b>CATALOG NUMBER</b>	C25DNF330C
<b>UPC</b>	782116311361
<b>PRODUCT LENGTH/DEPTH</b>	3.35 in
<b>PRODUCT HEIGHT</b>	3.75 in
<b>PRODUCT WIDTH</b>	2.4 in
<b>PRODUCT WEIGHT</b>	1.3 lb
<b>WARRANTY</b>	1 year
<b>COMPLIANCES</b>	RoHS Compliant
<b>CERTIFICATIONS</b>	UL Recognized CSA Certified UL Listed file E1491 (Guide Number NLDX2)



Powering Business Worldwide

## Product specifications

<b>AMPERAGE RATING</b>	30A
<b>NUMBER OF POLES</b>	Three-pole
<b>OPTIONS</b>	Global listed
<b>TYPE</b>	Non-reversing
<b>AUXILIARY CONTACTS</b>	Quick connect (side-by-side)
<b>COIL</b>	440-480 Vac, 50/60 Hz
<b>COIL VOLTAGE</b>	277 Vac, 60 Hz
<b>ENCLOSURE</b>	Open with metal mounting plate
<b>FRAME SIZE</b>	15-50 A, two-pole and three-pole
<b>INDUCTIVE FULL LOAD</b>	30 A
<b>MODEL</b>	Contactactor
<b>RESISTIVE LOAD</b>	40 A
<b>SERIES</b>	D1
<b>TERMINALS</b>	Box lugs (posidrive setscrew)
<b>CONNECTION</b>	Quick

## Resources

### SPECIFICATIONS AND DATASHEETS

[Eaton Specification Sheet - C25DNF330C](#)

**PROJECT NAME:**

**PROJECT NUMBER:**

**PREPARED BY:**

**DATE:**



### Eaton Corporation plc

Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information.



# Specifications



Photo is representative



## Eaton C25DNF330C

Eaton definite purpose contactor, Quick, 30A, 208-240 Vac at 50/60 Hz, Open with metal mounting plate, 15-50A, two- or 3P, 15-50A, two- and 3P, Contactor, 3P, Global ratings, Box lugs (posidrive setscrew) and quick connect terminals

### General specifications

<b>PRODUCT NAME</b>	Eaton definite purpose contactor
<b>CATALOG NUMBER</b>	C25DNF330C
<b>UPC</b>	782116311361
<b>PRODUCT LENGTH/DEPTH</b>	3.35 in
<b>PRODUCT HEIGHT</b>	3.75 in
<b>PRODUCT WIDTH</b>	2.4 in
<b>PRODUCT WEIGHT</b>	1.3 lb
<b>WARRANTY</b>	1 year
<b>COMPLIANCES</b>	RoHS Compliant
<b>CERTIFICATIONS</b>	UL Recognized CSA Certified UL Listed file E1491 (Guide Number NLDX2)



Powering Business Worldwide

## Product specifications

<b>AMPERAGE RATING</b>	30A
<b>NUMBER OF POLES</b>	Three-pole
<b>OPTIONS</b>	Global listed
<b>TYPE</b>	Non-reversing
<b>AUXILIARY CONTACTS</b>	Quick connect (side-by-side)
<b>COIL</b>	440-480 Vac, 50/60 Hz
<b>COIL VOLTAGE</b>	277 Vac, 60 Hz
<b>ENCLOSURE</b>	Open with metal mounting plate
<b>FRAME SIZE</b>	15-50 A, two-pole and three-pole
<b>INDUCTIVE FULL LOAD</b>	30 A
<b>MODEL</b>	Contactactor
<b>RESISTIVE LOAD</b>	40 A
<b>SERIES</b>	D1
<b>TERMINALS</b>	Box lugs (posidrive setscrew)
<b>CONNECTION</b>	Quick

## Resources

### SPECIFICATIONS AND DATASHEETS

[Eaton Specification Sheet - C25DNF330C](#)

**PROJECT NAME:**

**PROJECT NUMBER:**

**PREPARED BY:**

**DATE:**



### Eaton Corporation plc

Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information.

