

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

201 North East 20th Ave. 76067-0000, TX Mineral Wells Phone: 940-325-5503 Fax: 940-325-5544



A STATE OF THE PARTY OF THE PAR	
and the same of th	

C4 #4 Cu Long B Nsi Industries	arrel Compression Butt Splice
Catalog Number	C4
Manufacturer	Nsi Industries
Description	Compression Splice Connector, #6 Awg Conductor Size, #4 Awg Conductor Size, Non-Insulated, Copper Conductor Material, Gray Insulation Color, 2 Conductors, +90 °C Operating Temperature, 1.752 In Overall Length, Compression Terminal, 600 V, 0.052 LB/Ea
Weight per unit	0.0520 (lbs/each)
Product Category	Large Terminals & Connectors
itures	
Material	Copper
Number of Conductors	2

Feat

Material	Copper	
Number of Conductors	2	
Poles	1	
Voltage Rating	600 V	
Warranty	1 YEAR	

Material, Color, and Finish

Color	Gray
Finish	Tin Plated

Dimensions and Weight

J	
Size	L=1.75 - OD=.340 - ID=.250

Descriptions

Description	#4 CU LONG BARREL COMPRESSION BUTT SPLICE
extra long description	NSI C-4 4 AWG Copper Long Barrel Sp
Features	Long Barrel TinnedCopperSplice4 AWG Long Barrel Tinned
	CopperSplices is a type of copper compression connector that is
	produced from high conductivity copper tubing. They are
	tin-plated to provide corrosion resistance and are marked with
	die index and color coded for easy reference. Listed for 35KV
	maximum when properly installed.

Manufacturer Information

GTIN	00662381037510
UPC	662381037510

Taxonomies, Classifications, and Categories

Category Description	Comp & Mech Lugs and Butt Splices
Туре	Long Barrel - CU Splice



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

201 North East 20th Ave. 76067-0000, TX Mineral Wells Phone: 940-325-5503 Fax: 940-325-5544

_	-	-	ĸ	-	,		
	a	۱.	ĸ	•			

Carton	1	
Package	100	
Weight Per each	0.052	

Uses, Certifications, and Standards

Application	Terminate, Splice, Tap Power Connectors
environmental conditions	90 C
standard	UL486A/B, UL467 (8 AWG -3/0 AWG)
Temperature Rating	90 C