



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

4510 East Hwy 377
76049-0000, TX Granbury
Phone: 817-573-0675
Fax: 817-573-0776



CARS15TRWH Claro 15A Receptacle Tamper Resistant White

Lutron

Catalog Number	CARS15TRWH
Manufacturer	Lutron
Description	Lutron Claro Tamper-Resistant Duplex Receptacle, 15 Amp, White
Weight per unit	0.1500 (lbs/each)
Product Category	Gen Purpose Recept & Surge Pro

Features

amperage rating	15
connection	Screw Terminal
insulation	Plastic
Material	Plastic/Metal
Number of Wires	3,4,5
Poles	2
Voltage Rating	125
Wattage	1875
Wire Size	10 to 14

Material, Color, and Finish

Finish	Gloss
--------	-------

Dimensions and Weight

Size	4.69 x 2.94;119 x 75
------	----------------------

Descriptions

Description	CLARO 15A RECEPTACLE TAMPER RESISTANT WHITE
extra long description	LUT CARS-15-TR-WH CA 15A TAMPER RES
Features	Coordinate Lutron lighting controls and switches with Lutron Claro receptacles to complement your clients' decor. This receptacle features a permanently installed internal tamper-resistant shutter mechanism, capable of resisting insertion of foreign elements into the receptacle openings. Install with screw terminals or push-in connections. Available in 7 Gloss colors and 20 Satin colors, Lutron receptacles become beautiful accessories that let you coordinate and customize the look of each room in any home.
Long Description	Lutron Claro Tamper-Resistant Duplex Receptacle, 15 Amp, White
Product Type	Ca 15A Tamper Resist Recp White
Special Features	Includes shutter mechanism (shutters are white). Wallplate sold separately.



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

4510 East Hwy 377
76049-0000, TX Granbury
Phone: 817-573-0675
Fax: 817-573-0776

Manufacturer Information

Brand	Lutron
GTIN	00027557618267
Manufacturers Part Number	CARS-15-TR-WH
UPC	027557618267

Taxonomies, Classifications, and Categories

Category Description	Residential receptacles
Type	Tamper-resistant receptacle

Packaging

Carton	1
Package	24
Weight Per each	0.15

Uses, Certifications, and Standards

environmental conditions	0 to 90% humidity, non-condensing
Mounting	WALLBOX
standard	UL
Temperature Rating	32 to 104