Specifications



Photo is representative

Eaton CDR6034

Eaton Crouse-Hinds series PowerMate CDR receptacle, 60A, Three-wire, four-pole, Style 2, Copper-free aluminum, 600 Vac/250 Vdc

| General specifications | |
|-------------------------|---|
| PRODUCT NAME | Eaton Crouse-Hinds series PowerMate CDR receptacle |
| CATALOG NUMBER | CDR6034 |
| UPC | 662276276918 |
| PRODUCT LENGTH/DEPTH | 4.25 in |
| PRODUCT HEIGHT | 4.5 in |
| PRODUCT WIDTH | 4.5 in |
| PRODUCT WEIGHT | 2.2 lb |



Certifications and compliances

AREA CLASSIFICATION Ordinary/Non-Hazardous

Product specifications

AMPERAGE RATING

60A

| | Locations |
|----------------|-----------|
| STANDARDS TYPE | NEC/CEC |
| NEMA RATING | 4X |

| GROUNDING TYPE | Style 2 |
|----------------|-----------------------|
| CONFIGURATION | Three-wire, four-pole |
| VOLTAGE RATING | 600 Vac/250 Vdc |
| MATERIAL | Copper-free aluminum |

| Resources | |
|----------------------------------|--|
| 3D CAD DRAWING PACKAGE | Eaton Crouse-Hinds CDR6034 3D drawing |
| BROCHURES | PowerMate Drilling Pin and Sleeve Devices brochure |
| CATALOGS | PowerMate Drilling Pin and Sleeve Devices catalog page |
| CERTIFICATION REPORTS | PowerMate Drilling Pin and Sleeve Devices UL certification (Receptacles) |
| INSTALLATION INSTRUCTIONS | IF 1834 - PowerMate Pin and Sleeve Devices with Nested Bushing |
| | IF 1632 - 30, 60, 100 and 150A PowerMate Pin and Sleeve Devices |
| SPECIFICATIONS AND DATASHEETS | PowerMate Connectors Eaton Specification Sheet - CDR6034 |

| PROJECT NAME: | |
|------------------------|--|
| PROJECT NUMBER: | |
| PREPARED BY: | |
| DATE: | |
| | |



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information.

© 2025 Eaton. All Rights

Reserved.



Specifications



Photo is representative

Eaton CDR6034

Eaton Crouse-Hinds series PowerMate CDR receptacle, 60A, Three-wire, four-pole, Style 2, Copper-free aluminum, 600 Vac/250 Vdc

| General specifications | |
|-------------------------|---|
| PRODUCT NAME | Eaton Crouse-Hinds series PowerMate CDR receptacle |
| CATALOG NUMBER | CDR6034 |
| UPC | 662276276918 |
| PRODUCT LENGTH/DEPTH | 4.25 in |
| PRODUCT HEIGHT | 4.5 in |
| PRODUCT WIDTH | 4.5 in |
| PRODUCT WEIGHT | 2.2 lb |



Certifications and compliances

AREA CLASSIFICATION Ordinary/Non-Hazardous

Product specifications

AMPERAGE RATING

60A

| | Locations |
|----------------|-----------|
| STANDARDS TYPE | NEC/CEC |
| NEMA RATING | 4X |

| GROUNDING TYPE | Style 2 |
|----------------|-----------------------|
| CONFIGURATION | Three-wire, four-pole |
| VOLTAGE RATING | 600 Vac/250 Vdc |
| MATERIAL | Copper-free aluminum |

| Resources | |
|----------------------------------|--|
| 3D CAD DRAWING PACKAGE | Eaton Crouse-Hinds CDR6034 3D drawing |
| BROCHURES | PowerMate Drilling Pin and Sleeve Devices brochure |
| CATALOGS | PowerMate Drilling Pin and Sleeve Devices catalog page |
| CERTIFICATION REPORTS | PowerMate Drilling Pin and Sleeve Devices UL certification (Receptacles) |
| INSTALLATION INSTRUCTIONS | IF 1834 - PowerMate Pin and Sleeve Devices with Nested Bushing |
| | IF 1632 - 30, 60, 100 and 150A PowerMate Pin and Sleeve Devices |
| SPECIFICATIONS AND DATASHEETS | PowerMate Connectors Eaton Specification Sheet - CDR6034 |

| PROJECT NAME: | |
|------------------------|--|
| PROJECT NUMBER: | |
| PREPARED BY: | |
| DATE: | |
| | |



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information.

© 2025 Eaton. All Rights

Reserved.

