

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



CG3750S 1/2" STL T-Tube.37 Appleton/Oz Gedney

Catalog Number	CG3750S
Catalog Number Manufacturer	Apploton/Oz Codnov
Description	Straight Liquidtight Strain Relief Connector, Size: 1/2 In,
Description	Conductor Range: 3/8 - 1/2 In, Material: Machined Steel, Color: Purple Label, Nema Rating: Nema 3R, Connection: Threaded Hub Dimensions: 1-1/4 In Height, Standard: Class I, Div
Weight per unit	0.2100 (lbs/each)
Product Category	Cable & Cord Grips
eatures	
connection	Threaded Hub
aterial, Color, and Finish	
Color	Purple
mensions and Weight	
Size	1/2
escriptions	
Description	1/2" STL T-TUBE.37
extra long description	APP CG-3750S 1/2 IN STL L-T CRD&CBL
Long Description	Straight Liquidtight Strain Relief Connector, Size: 1/2 IN, Conductor Range: 3/8 - 1/2 IN, Material: Machined Steel, Color: Purple Label, Nema Rating: NEMA 3R, Connection: Threaded Hub, Dimensions: 1-1/4 IN Height, Standard: Class I, Div
Product Type	1/2 In STL L-T CRD&CBL Conn
Special Features	Color coded identification label clearly states the catalog numbe and minimum-maximum cable diameter range for which the connector is designed; For use in wet or dry locations sealing electrical connections against dust and dirt, oil, water or other atmosphere containing moisture; Machined steel cap; Neoprene sealing grommet; Neoprene sealing grommet firmly but safely grips cable jacket providing strain relief while protecting internal wiring connections against external tension on cable or cord; Steel or Tefl
anufacturer Information	
Brand	Appleton
GTIN	00781381455626
Manufacturers Part Number	CG-3750S
UPC	781381455626



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Cate	egories
Category Description	CORD CONNECTORS & CORD GRIPS
Туре	Straight Liquidtight Strain Relief Connector
Packaging	
Carton	1
Package	25
Weight Per each	0.21
Uses, Certifications, and Standards	
Application	For Flexible Type Neoprene, Hypalon And PVC Jacketed Power Or Control Cord And Cable
nema rating	3R
standard	Class I, Division 2, Class II, Division 1 And 2 Class III, UL 514B, E14817, CSA C22.2 No. 18.3, 065178