

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2805 Poplar 75402-0000, TX Greenville Phone: 903-454-3354 Fax: 903-454-8926



CG50100 1" Alu ST Cord Conn Appleton/Oz Gedney

Catalog Number	CG50100
Manufacturer	Appleton/Oz Gedney
Description	Straight Liquidtight Strain Relief Connector, Size: 1 In, Conductor Range: 1/2 - 5/8 In, Material: Aluminum, Color: Pink Label, Nema Rating: Nema 3R, Connection: Threaded Hub, Dimensions: 1.38 In Height, Standard: Class I, Division 2, CL
Weight per unit	0.1500 (lbs/each)
Product Category	
Features	
connection	Threaded Hub
Material, Color, and Finish Color	Pink
Dimensions and Weight Size	1
Descriptions	
Description	1" ALU ST CORD CONN
extra long description	APP CG-50100 1 IN ALUM L-T CRD&CBL
Long Description	Straight Liquidtight Strain Relief Connector, Size: 1 IN, Conductor Range: 1/2 - 5/8 IN, Material: Aluminum, Color: Pink Label, Nema Rating: NEMA 3R, Connection: Threaded Hub, Dimensions: 1.38 IN Height, Standard: Class I, Division 2, Cl
Product Type	1 In Alum L-T CRD&CBL Conn
Special Features	Color coded identification label clearly states the catalog number and minimum-maximum cable diameter range for which the connector is designed; Copper free (4/10 of 1 PCT or less) aluminum cap; For use in wet or dry locations sealing electrical connections against dust and dirt, oil, water or other atmosphere containing moisture; Neoprene sealing grommet; Neoprene sealing grommet firmly but safely grips cable jacket providing strain relief while protecting internal wiring connections against external tension
Manufacturer Information	
Brand	Appleton
GTIN	00781381191708
Manufacturers Part Number	CG-50100
UPC	781381191708



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2805 Poplar 75402-0000, TX Greenville Phone: 903-454-3354 Fax: 903-454-8926

Taxonomies, Classifications, and	Categories
Category Description	CORD CONNECTORS & CORD GRIPS
Туре	Straight Liquidtight Strain Relief Connector
Packaging	
Carton	1
Package	10
Weight Per each	0.15
Uses, Certifications, and Standard	ds
Application	For Flexible Type Neoprene, Hypalon And PVC Jacketed Power Or Control Cord And Cable
nema rating	3R
standard	Class I, Division 2, Class II, Division 1 And 2 Class III, UL 514B,

E14817, CSA C22.2 No. 18.3, 065178