



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



CG5075S 3/4" STR STL Cord Conn .500-.750 Dia *Appleton/Oz Gedney*

Catalog Number	CG5075S
Manufacturer	Appleton/Oz Gedney
Description	Straight Liquidtight Strain Relief Connector, Size: 3/4 In, Conductor Range: 1/2 - 5/8 In, Material: Machined Steel, Color: Pink Label, Nema Rating: Nema 3R, Connection: Threaded Hub, Dimensions: 1-1/4 In Height, Standard: Class I, Divis
Weight per unit	0.2500 (lbs/each)
Product Category	Cable & Cord Grips

Features

connection	Threaded Hub
------------	--------------

Material, Color, and Finish

Color	;/Pink
-------	--------

Dimensions and Weight

Size	3/4
------	-----

Descriptions

Description	3/4" STR STL CORD CONN .500-.750 DIA
extra long description	APP CG-5075S 3/4 IN STL L-T CRD AND
Long Description	Straight Liquidtight Strain Relief Connector, Size: 3/4 IN, Conductor Range: 1/2 - 5/8 IN, Material: Machined Steel, Color: Pink Label, Nema Rating: NEMA 3R, Connection: Threaded Hub, Dimensions: 1-1/4 IN Height, Standard: Class I, Divis
Product Type	3/4 In STL L-T CRD and CBL Conn
Special Features	Color coded identification label clearly states the catalog number and minimum-maximum cable diameter range for which the connector is designed;For use in wet or dry locations sealing electrical connections against dust and dirt, oil, water or other atmosphere containing moisture;Machined steel cap;Neoprene sealing grommet;Neoprene sealing grommet firmly but safely grips cable jacket providing strain relief while protecting internal wiring connections against external tension on cable or cord;Steel or Tefl

Manufacturer Information

Brand	Appleton
GTIN	00781381449373
Manufacturers Part Number	CG-5075S
UPC	781381449373



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Taxonomies, Classifications, and Categories

Category Description	CORD CONNECTORS & CORD GRIPS
Type	Straight Liquidtight Strain Relief Connector

Packaging

Carton	1
Package	25
Weight Per each	0.25

Uses, Certifications, and Standards

Application	For Flexible Type Neoprene, Hypalon And PVC Jacketed Power Or Control Cord And Cable
nema rating standard	3R Class I, Division 2, Class II, Division 1 And 2 Class III, UL 514B, E14817, CSA C22.2 No. 18.3, 065178