

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



CG608 CG Mle Straight 3/4 .440-.500 Pass & Seymour/Legrand

Catalog Number	CG608
Manufacturer	Pass & Seymour/Legrand
Description	Cord Grip Male Straight, 3/4-Inch NPT, 0.375-Inch-0.500-Inch
Weight per unit	2.1 (lbs/each)
Product Category	Cable & Cord Grips

Features

Cable Size	NPT Size: 3/4; Cable Dia. Range: 0.440-0.500
Cable Type	Various Types of Electrical Conductor/Cable
load	Strain Relief Grips are designed to prevent tension from being transferred to junctions and terminals on electrical cord, cable and conduit, therefore providing a more secure electrical structure.

Descriptions

Construction	Support and Strain Relief Grips, Various Types of Pulling
Description	CG MLE STRAIGHT 3/4 .440500
extra long description	P&S CG608 CG MLE STR 3/4 .440500
Long Description	Cord Grip Male Straight, 3/4-inch NPT, 0.375-inch-0.500-inch
Product Type	CG Mle STR 3/4 .440500
Special Features	Deluxe cord grips are woven of stainless steel mesh with an aluminum body for corrosion resistance. They are offered in single/double weave construction to help absorb direct pull, to resist flexing and binding, and to eliminate strain. They are recommended for indoor or outdoor use where subjected to moisture in the wiring of pendant stations, processing equipment, hand tools, and extension cord sets. Deluxe grips are

Manufacturer Information

Brand	LEGRAND-PASS & SEYMOUR
GTIN	00785007997477
Manufacturers Part Number	CG608
UPC	785007997477

Div. 1 & 2: and C

suitable for use in hazardous locations per Class I, Div. 2: Class II,

Taxonomies, Classifications, and Categories

Category Description	CORD CONNECTORS & CORD GRIPS
Туре	Flexcor® Deluxe Strain Relief Cord Grip - Straight Male

Packaging

Carton	1
Weight Per each	2.05

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards

Application	Industrial
Capacity	Various Cable Diameter Ranges
Mounting	Consult the Factory for Mounting Recommendations
standard	UL, CSA, UL/CSA Approval (consult factory)