

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

760 Ford St. 80915-0000, CO Colorado Springs Phone: 719-559-2456 Fax: 719-867-4287



CGB293 3/4" Dia Male Cord Grip (.250-.375) *Crouse-Hinds*

Catalog Number	CGB293
Manufacturer	Crouse-Hinds
Description	Cord Gland, Steel With Zinc Electroplate and Chromate Finish Coat (Body, Gland Nut); Neoprene (Bushing) Material, CGB Model, 0.25 to 0.375 In Cable/Cord Size, 2 In Length, 1.23 In Diameter, Straight Male Connection, 3/4 In Thread Size, -25 °C Operating Temperature, +40 °C Operating Temperature, 0.24 LB
Weight per unit	0.2400 (lbs/each)
Product Category	Cable & Cord Grips
Features	
connection	Male NPT
dimensions	2.0000 IN X 1.2300 IN X 1.2300 IN
Material, Color, and Finish	
Finish	Zinc Electroplated With Chromate Coated
Dimensions and Weight	
Size	3/4 in
Descriptions	
Description	3/4" DIA MALE CORD GRIP (.250375)
extra long description	CRS-H CGB293 3/4 NPT MALE CORD/CAB
Features	They are also listed for use with tray cable types TC, TC-ER,
	TC-ER-HLA, ITC, ITC-ER, ITC-HL, PLTC and PLTC-ER. When
	installed in accordance with NEC501.10(B)(4), CGB, CGD, CGE and
	CGFP non-armoured glands are suitable for use in Class I, Division
	2 hazardous locations. Crouse-Hinds series CGB, CGD, CGE and
	CGFP non-armoured glands are installed to provide a means for
	passing a cord, unarmoured cable or flexible conduit into an
	enclosure. The glands form an environmental seal for cord or unarmoured round
NAfa akuman linfa masaki an	unarmoureu rounu
Manufacturer Information Brand	Eaton
GTIN	00782274132303
LIDC	792274122202
Taxonomies, Classifications, and	CORD COMMENTATOR C CORD ORIDO
Category Description	
Type	Cable gianu



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

760 Ford St. 80915-0000, CO Colorado Springs Phone: 719-559-2456 Fax: 719-867-4287

				g

Carton	1	
Package	25	
Weight Per each	0.24	

Uses, Certifications, and Standards

Enclosure	Class I Div 2	
standard	UL (CANADA AND US), CUL	
Temperature Rating	-25 To 40 Deg C	