

# Specifications



Photo is representative



## Eaton CHM1N7N7NSU

Eaton pedestal mount metered, Metered-ring, 50A, Non-ground fault, Non-ground fault, Non-ground fault, Bottom, Surface, Circuits: 4, NEMA 5-20R2GFI, NEMA 14-50R, NEMA 5-20R2GFI, 250V

### General specifications

|                             |                                                                                                                                                                                  |
|-----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>PRODUCT NAME</b>         | Eaton pedestal mount metered                                                                                                                                                     |
| <b>CATALOG NUMBER</b>       | CHM1N7N7NSU                                                                                                                                                                      |
| <b>UPC</b>                  | 786685404264                                                                                                                                                                     |
| <b>PRODUCT LENGTH/DEPTH</b> | 7.25 in                                                                                                                                                                          |
| <b>PRODUCT HEIGHT</b>       | 31 in                                                                                                                                                                            |
| <b>PRODUCT WIDTH</b>        | 10 in                                                                                                                                                                            |
| <b>PRODUCT WEIGHT</b>       | 30 lb                                                                                                                                                                            |
| <b>WARRANTY</b>             | Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first. |
| <b>CERTIFICATIONS</b>       | UL Listed file E163588<br>UL 231                                                                                                                                                 |

## Product specifications

|                            |                  |
|----------------------------|------------------|
| TYPE                       | Metered-ring     |
| CIRCUIT BREAKER POSITION 1 | Non-ground fault |
| CIRCUIT BREAKER POSITION 2 | Non-ground fault |
| CIRCUIT BREAKER POSITION 3 | Non-ground fault |
| RECEPTACLE CENTER          | NEMA 5-20R2GFI   |
| RECEPTACLE LEFT            | NEMA 14-50R      |
| RECEPTACLE RIGHT           | NEMA 5-20R2GFI   |
| FEED TYPE                  | Bottom           |
| MOUNTING                   | Surface          |
| NUMBER OF CIRCUITS         | 4                |

## Resources

|                               |                                                                                   |
|-------------------------------|-----------------------------------------------------------------------------------|
| CATALOGS                      | <a href="#">Residential and Light Commercial, Power Pedestals, Volume 1 Tab 5</a> |
| SPECIFICATIONS AND DATASHEETS | <a href="#">Eaton Specification Sheet - CHM1N7N7NSU</a>                           |

---

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:

---



### Eaton Corporation plc

Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

