


## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

320 SW 28TH ST 72712-0000, AR Bentonville Phone: 479-250-1930 Fax: 479-250-1931





Weight Per each

## CHN220GF CH 5MA Gfci 2P 20A 120/240V 10kaic Eaton Corp

Eaton Corp	
Catalog Number	CHN220GF
Manufacturer	Eaton Corp
Description	Eaton CH Gfci Circuit Breaker, Plug-In Circuit Breaker, 20 A, 10 Kaic, Two-Pole, 120/240 V, CH, Common, GFI, 5 Ma
Weight per unit	0.9500 (lbs/each)
Product Category	In Circuit Breakers
Features	
dimensions	3.5000 IN X 3.5000 IN X 2.1000 IN
interrupt rating	10
Poles	2
Voltage Rating	120/240 V
Descriptions	
Description	CH 5MA GFCI 2P 20A 120/240V 10KAIC
extra long description	ETN CHN220GF CH 5mA GFCI, 2P, 20A,
Features	Eaton's residential CH circuit breakers provide premium overload
	protection. The Type CH circuit breakers trip to the OFF position,
	eliminating nuisance callbacks. The CHF family also includes a trip
	flag to differentiate between a trip and the breaker being turned
	off. The thermal-magnetic trip curve avoids nuisance tripping on
	mild overloads while reacting almost instantaneously to severe
	short-circuit conditions. Multiple breakers have an internal
Long Description	common trip connection to operate all poles simultaneous
	Eaton CH GFCI circuit breaker,Plug-in circuit breaker,20 A,10 kAIC,Two-pole,120/240 V,CH,Common,GFI,5 mA
Product Type	CH 5MA Gfci, 2P, 20A, 120/240V, 10kaic
Manufacturer Information	011 31VI/1 G1G1, 21 / 20/1, 120/240 V, 10/10
Brand	Eaton
GTIN	00786689217228
Manufacturers Part Number	CHN220GF
UPC	786689217228
Taxonomies, Classifications, and C	<del>-</del>
Type	GFCI circuit breakers
Availability	
Status	Inactive
Packaging	
Carton	1

0.95

## Uses, Certifications, and Standards

cs, oci tilications, and st	andaras
Application	Datacenters - IT Space: CI and Hyper ConvergedGeneration -
	Renewable Energy - Alternative EnergyGeneration - Conventional
	Energy - Conventional EnergyMarine Vessels and Equipment -
	Marine Vessels and Equipment - OtherOther
standard	UL 489