



CPP516 20 Amp 125-250VAC 2W-3P Plug

Crouse-Hinds

Catalog Number	CPP516
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Arktite CPP Plug, 20A, 0.312-0.625" Cable Diameter, Two-Wire, Three-Pole, Brass Contacts, 60 Hz, Style 2, 1 HP, Copper-Free Aluminum, Factory Sealed, Delayed Action Circuit Breaking, 125-250 Vac/18 VDC
Weight per unit	0.8000 (lbs/each)
Product Category	Pin & Sleeve Devices

Features

amperage rating	100
Cord Type	0.875 To 1.700 In
dimensions	8.3800 IN X 1.7500 IN X 1.7500 IN
Material	Copper-Free Aluminum
Poles	1
Voltage Rating	600 VAC AT 50 TO 400 HZ, 250 VDC
Wire Size	4 To 1 AWG (Building), 4 To 2 AWG (Extra Flex)

Dimensions and Weight

Length	10-1/8
--------	--------

Descriptions

Description	20 AMP 125-250VAC 2W-3P PLUG
extra long description	CRS-H CPP516 20A 2W3P ARK PLG AL HD
Features	Crouse-Hinds series Arktite CPS and CPP explosionproof receptacles and plugs are used with portable electrically operated devices such as motor generator sets, compressors, conveyors, portable tools and lighting systems. CPS receptacles are equipped with a rotating mechanism which prevents complete withdrawal of the CPP plug in one continuous movement. This delayed action feature permits the plug to be used as an emergency push-pull switch. Available in 20A and 30A configurations.
Long Description	Eaton Crouse-Hinds series Arktite CPP plug, 20A, 0.312-0.625" cable diameter, Two-wire, three-pole, Brass contacts, 60 Hz, Style 2, 1 HP, Copper-free aluminum, Factory sealed, Delayed action circuit breaking, 125-250 Vac/18 Vdc
Product Type	20A 2W3P Ark PLG AL HDL .312 to .625
Special Features	Watertight, Grounding Style 1, NEMA 4 Enclosure, Reverse Interior



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

8620 E 34th St N
67226-0000, KS Wichita
Phone: 316-247-8220
Fax: 000-000-0000

Manufacturer Information

Brand	EATON CROUSE-HINDS SERIES
GTIN	00782274175102
Manufacturers Part Number	CPP516
UPC	782274175102

Taxonomies, Classifications, and Categories

Category Description	Pin & Sleeve Devices
Type	PLUG

Packaging

Carton	1
Package	2
Weight Per each	0.8

Uses, Certifications, and Standards

Application standard	Ind Facilities & Factories - Facility: Power Distribution and Control UL 514, UL 1010, UL 1682, CSA C22.2
----------------------	--