



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



CS8264C Locking Conn, 50A 250V, 2P3W *Hubbell Wiring Devices*

Catalog Number	CS8264C
Manufacturer	Hubbell Wiring Devices
Description	Locking Devices, Twist-Lock®, Industrial, Female Connector Body, 50A 250V, 2-Pole 3-Wire Grounding, Non-Nema, Screw Terminal, Black and White
Weight per unit	0.3340 (lbs/each)
Product Category	Plugs, Connectors, Inlets, Out

Features

amperage rating	50
connection	Pressure Screw Terminal
Current Rating	50
insulation	Insulated Body
Material	Nylon
Number of Conductors	3
pallet quantity	1190
Poles	2-Pole
Voltage Rating	250

Material, Color, and Finish

Color	Black;White
-------	-------------

Dimensions and Weight

Size	6.50 in x 2.56 in x 2.50 in
------	-----------------------------

Descriptions

Description	LOCKING CONN, 50A 250V, 2P3W
extra long description	HWDC CS8264C LOCKING CONN, 50A 250V
Features	Hubbell's 50 Amp Twist-Lock® Devices feature a heavy-duty design and super-tough nylon housing built for heavy-duty applications and impact resistance, even in the harshest environments. Their rigid construction restricts contact distortion, minimizing the possibility of mating dissimilar devices. The cord grip's offset gripping jaws securely hold the conductors and the cord jacket for excellent strain relief.
Long Description	Locking Devices, Twist-Lock®, Industrial, Female Connector Body, 50A 250V, 2-Pole 3-Wire Grounding, Non-NEMA, Screw Terminal, Black and White
Product Type	Locking Conn, 50A 250V, 2P3W
Special Features	Standard Product



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Manufacturer Information

Brand	WIRING DEVICE-KELLEMS
GTIN	00783585828466
Manufacturers Part Number	CS8264C
UPC	783585828466

Taxonomies, Classifications, and Categories

Category Description	NEMA RATED TURNLOK PLUGS, CONNECTORS, & RECEPTICLES
Type	Connector Body

Packaging

Carton	1
Weight Per each	0.334

Uses, Certifications, and Standards

Application	Heavy Duty Industrial
environmental conditions	Indoor Dry unless protected by additional means
Mounting	Cord
nema rating	Non-NEMA
standard	Certified to CSA C22.2 No.42;Listed to UL 498