


Industrial grade 50A locking devices

Product description

2-pole, 3-wire grounding
50A, 250V/AC
Non-NEMA, California standard




Receptacle

Plug



CS8265



CS8277

California standard plugs & connectors

Rating A	V/AC	Description	Cord diameter	Color	Plug catalog no.	Connector catalog no.		
50	250	Pro grip nylon California standard	0.44-1.06" (11.1-26.0mm)	RD & BK	☐ CS8265EX	☐ CS8264EX	•	•
		Armored California standard	0.68-1.13" (17.3-28.6mm)	Steel	☐ CS8265	☐ CS8264	•	•

California standard grade receptacles

Rating A	V/AC	Description	Color	Single receptacle		
50	250	California standard receptacles	BK	☐ CS8269	•	•

California standard flanged inlets

Rating A	V/AC	Description	Color	Flanged inlet	Flanged inlet w/ lid		
50	250	California standard flanged inlets	Steel	☐ CS8275	☐ CS8277	•	•

Accessories for 50A California standard locking devices

Description	Color suffix	Catalog no.		
Weather protective glass-filled nylon, w/ lift lid cover	BK, CR, GY	☐ 7788__	•	•
Weather protective diecast aluminum, w/ lift lid cover		☐ 7770	•	
Weather protective boot for 50A armored plug		☐ 7716	•	
Weather protective boot for 50A armored connector		☐ 7717	•	
Weather protective boot for 50A pro grip plug		☐ 7716EX	•	
Weather protective boot for 50A pro grip connector		☐ 7717EX	•	



7788CR
Corrosion
resistant



7770



7716



7717



7716EX



7717EX

Dimensional information:

C-80, C-81

Plug & connector specification information:

50A: C-92

Receptacle specification information:

50A: C-92

Flanged inlet & flanged outlet specification information:

50A: C-92

Color ordering information:

For ordering devices, include Catalog no. followed by the Color suffix: BK (Black), GY (Gray), RD (Red), Y or CR (Yellow)

(Black)	(Gray)	(Red)	(Yellow)	(Steel)

Compliances, specifications and availability are subject to change without notice.


Indicates NAFTA compliant - Page Q-32

RoHS compliant - Page Q-32

Industrial grade 50A locking devices

Product description

2-pole, 3-wire grounding
50A, 250V/AC
Non-NEMA, California standard




Receptacle

Plug



CS8265



CS8277

California standard plugs & connectors

Rating A	V/AC	Description	Cord diameter	Color	Plug catalog no.	Connector catalog no.		
50	250	Pro grip nylon California standard	0.44-1.06" (11.1-26.0mm)	RD & BK	☐ CS8265EX	☐ CS8264EX	•	•
		Armored California standard	0.68-1.13" (17.3-28.6mm)	Steel	☐ CS8265	☐ CS8264	•	•

California standard grade receptacles

Rating A	V/AC	Description	Color	Single receptacle		
50	250	California standard receptacles	BK	☐ CS8269	•	•

California standard flanged inlets

Rating A	V/AC	Description	Color	Flanged inlet	Flanged inlet w/ lid		
50	250	California standard flanged inlets	Steel	☐ CS8275	☐ CS8277	•	•

Accessories for 50A California standard locking devices

Description	Color suffix	Catalog no.		
Weather protective glass-filled nylon, w/ lift lid cover	BK, CR, GY	☐ 7788__	•	•
Weather protective diecast aluminum, w/ lift lid cover		☐ 7770	•	
Weather protective boot for 50A armored plug		☐ 7716	•	
Weather protective boot for 50A armored connector		☐ 7717	•	
Weather protective boot for 50A pro grip plug		☐ 7716EX	•	
Weather protective boot for 50A pro grip connector		☐ 7717EX	•	



7788CR
Corrosion
resistant



7770



7716



7717



7716EX



7717EX

Dimensional information: C-80, C-81

Plug & connector specification information:

50A: C-92

Receptacle specification information:

50A: C-92

Flanged inlet & flanged outlet specification information:

50A: C-92

Color ordering information:

For ordering devices, include Catalog no. followed by the Color suffix: BK (Black), GY (Gray), RD (Red), Y or CR (Yellow)

(Black)	(Gray)	(Red)	(Yellow)	(Steel)

Compliances, specifications and availability are subject to change without notice.

Indicates NAFTA compliant - Page Q-32

RoHS compliant - Page Q-32