



## CS8364C Locking Conn, 50A 3PH 250V, 3P4W

*Hubbell Wiring Devices*

Catalog Number	CS8364C
Manufacturer	Hubbell Wiring Devices
Description	Locking Devices, Twist-Lock®, Industrial, Female Connector Body, 50A 3-Phase Delta 250V Ac, 3-Pole 4-Wire Grounding, Non-Nema, Screw Terminal, Black and White
Weight per unit	0.3380 (lbs/each)
Product Category	Plugs, Connectors, Inlets, Out

### Features

amperage rating	50
connection	Pressure Screw Terminal
Current Rating	50
insulation	Insulated Body
Material	Nylon
Number of Conductors	4
pallet quantity	1190
Poles	3-Pole
Voltage Rating	3-Phase Delta 250

### Material, Color, and Finish

Color	Black;White
-------	-------------

### Dimensions and Weight

Size	6.50 in x 2.56 in x 2.50 in
------	-----------------------------

### Descriptions

Description	LOCKING CONN, 50A 3PH 250V, 3P4W
extra long description	HWDK CS8364C LOCKING CONN, 50A 3PH
Features	Hubbell's 50 Amp Twist-Lock® Devices feature a heavy-duty design and super-tough nylon housing built for heavy-duty applications and impact resistance, even in the harshest environments. Their rigid construction restricts contact distortion, minimizing the possibility of mating dissimilar devices. The cord grip's offset gripping jaws securely hold the conductors and the cord jacket for excellent strain relief.

Long Description	Locking Devices, Twist-Lock®, Industrial, Female Connector Body, 50A 3-Phase Delta 250V AC, 3-Pole 4-Wire Grounding, Non-NEMA, Screw Terminal, Black and White
------------------	--

Product Type	Locking Conn, 50A 3PH 250V, 3P4W
Special Features	Standard Product



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1501 Heritage Parkway Suite 101  
76063-0000, TX Mansfield  
Phone: 682-518-7272  
Fax: 682-518-7255

## Manufacturer Information

Brand	WIRING DEVICE-KELLEMS
GTIN	00783585829104
Manufacturers Part Number	CS8364C
UPC	783585829104

## Taxonomies, Classifications, and Categories

Category Description	NEMA RATED TURNLOK PLUGS, CONNECTORS, & RECEPTICLES
Type	Connector Body

## Packaging

Carton	1
Package	10
Weight Per each	0.338

## Uses, Certifications, and Standards

Application	Heavy Duty Industrial
environmental conditions	Indoor Dry unless protected by additional means
Mounting	Cord
nema rating	Non-NEMA
standard	Certified to CSA C22.2 No.42; Listed to UL 498