


ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

520 Equity Ave 72032-0000, AR Conway Phone: 501-336-8444





Type

CTCL153PWH Contour 150W Led 3WAY White

| Alm | |
|---|---|
| Catalog Number | CTCL153PWH |
| Manufacturer | Lutron |
| Description | Dimmer, On/Off Rocker Switch, 150 W;6000 W, 60 HZ, Dimmable CFL/Led;Incandescent/Halogen Lamp, Wall Mount, 2.94 In Length, 2.75 In Width, 4.69 In Height, White, +32 °F Operating Temperature, +104 °F Operating Temperature, 1 Yr Warranty, 0.15 LB/Ea |
| Weight per unit | 0.1500 (lbs/each) |
| Product Category | Lighting Dimmers |
| eatures | |
| actuator | Rocker/Slide |
| connection | Wire Leads |
| Connection Type | Wire Leads |
| insulation | Plastic |
| Material | Plastic/Metal |
| media | Yes |
| Poles | 1 |
| Voltage Rating | 120 |
| Wattage | 600 |
| Vlaterial, Color, and Finish Finish | Gloss |
| | |
| Dimensions and Weight Size | 4.69 x 2.94;119 x 75 |
| Descriptions | |
| Description | CONTOUR 150W LED 3WAY WHITE |
| extra long description | LUT CTCL-153P-WH CONTOUR CFL/LED WH |
| Special Features | Controls 150 W LED/CFL (screw-base) or 600 W |
| | incandescent/halogen loads. Rocker switch returns light to light level indicated by slider. Provides reliable dimming of dimmable LEDs/CFLs, as well as halogens and incandescents. |
| Manufacturer Information | |
| GTIN | 00027557002967 |
| UPC | 027557002967 |
| Taxonomies, Classifications, and Category Description | Categories Residential dimmers, motion sensors, controls, & photo cells |
| | |

Dimmer with on/off switch, 3-way/single-pole



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

520 Equity Ave 72032-0000, AR Conway Phone: 501-336-8444 Fax: 501-329-5636

| | / A A | 100 |
|-----|-------|------|
| Pac | K AN | |
| u | NU | HILL |
| | | |
| | | |

| Carton | 1 | |
|-----------------|------|--|
| Package | 24 | |
| Weight Per each | 0.15 | |

Uses, Certifications, and Standards

| Application | Lighting Control | |
|--------------------------|------------------|--|
| Enclosure | Plastic | |
| environmental conditions | Indoor use only | |
| Mounting | WALLBOX | |
| Operating Temperature | 32 to 104 | |
| standard | UL, CSA | |