


ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

3804 W. Esthner Avenue 67213-0000, KS Wichita Phone: 316-854-0028 Fax: 316-854-0029





Category Description

Type

DH222NGK 60A/2P HD Fusible Safety Switch W/Neut 240V Nema 1 *Eaton Corp*

Catalog Number	DH222NGK
Manufacturer	Eaton Corp
Description	Eaton Heavy Duty Single-Throw Fused Safety Switch, 60 A, Nema 1, Painted Steel, Class H, Fusible With Neutral, Two-Pole, Three-Wire, 240 V, Max HP: 3, 7.5 HP/10, 15 HP/10 HP (1, 3PH @ STD Fuse/Time Delay/250 VDC), #14-#2 Cu/Al
Weight per unit	17.0 (lbs/each)
Product Category	Fusible Heavy Duty Safety Swit
eatures	
amperage rating	60
Material	Painted Steel
media	Yes
Poles	2
Voltage Rating	240V
Dimensions and Weight	
Depth	16.5
Height	8.31
Width	9.12
Descriptions	
Description	60A/2P HD FUSIBLE SAFETY SWITCH W/NEUT 240V NEMA 1
extra long description	ETN DH222NGK 60A/2P HD FUSIBLE Sfty
Features	Eaton's heavy-duty safety switches provide a highly visible mean of disconnect to help improve personnel safety and equipment protection. Additionally, they're Ideal for applications where reliable performance, safety, and service continuity are critical.
Long Description	Eaton Heavy duty single-throw fused safety switch, 60 A, NEMA 1, Painted steel, Class H, Fusible with neutral, Two-pole, Three-wire, 240 V, Max Hp: 3, 7.5 hp/10, 15 hp/10 hp (1,3PH @ Std fuse/time delay/250 Vdc), #14-#2 Cu/Al
Product Type	60A/2P HD Fusible Sfty SW W/Neut 240V N1
Manufacturer Information	
Brand	Eaton
GTIN	00782113205779
Manufacturers Part Number	DH222NGK
UPC	782113205779

DISCONNECTS

Fusible safety switch



standard

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

3804 W. Esthner Avenue 67213-0000, KS Wichita Phone: 316-854-0028 Fax: 316-854-0029

Packaging	
Carton	1
Weight Per each	17
Uses, Certifications, and Standards	
Application	Commercial / Institutional Buildings / Structures - Power
	Distribution and Controls
nema rating	1

CSA Certified, UL Listed, NEC 230.62 (C) Compliant Barrier