



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

201 South Persimmon Street
77375-6855, TX Tomball
Phone: 281-357-5300
Fax: 281-357-5005



DH364UWK 200A/3P HD Non-Fused Safety Switch 600V Nema 4X SS

Eaton Corp

Catalog Number	DH364UWK
Manufacturer	Eaton Corp
Description	Eaton Heavy Duty Single-Throw Non-Fused Safety Switch, Single-Throw, 200A, Nema 4X, Stainless Steel, Three-Pole, Three-Wire, 15 At 240 Vac TD 1 PH, 50 At 480 Vac TD 1 PH, 50 At 600 Vac TD 1 PH, 60 At 240 Vac TD 3 PH, Non-Fusible
Weight per unit	61.0 (lbs/each)
Product Category	Non-Fusible Heavy Duty Safety

Features

amperage rating	200
Material	Stainless Steel
media	Yes
Poles	Three-pole
Voltage Rating	600 V

Dimensions and Weight

Depth	11.5
Height	34.38
Width	16

Descriptions

extra long description	ETN DH364UWK 200A/3P HD NF Sfty Sw
Features	Eaton's heavy-duty safety switches provide a highly visible means of disconnect to help improve personnel safety and equipment protection. Additionally, they're Ideal for applications where reliable performance, safety, and service continuity are critical.
Long Description	Eaton Heavy duty single-throw non-fused safety switch, Single-throw, 200A, NEMA 4X, Stainless steel, Three-pole, Three-wire, 15 at 240 Vac TD 1 Ph, 50 at 480 Vac TD 1 Ph, 50 at 600 Vac TD 1 Ph, 60 at 240 Vac TD 3 Ph, Non-Fusible
Product Type	200A/3P HD NF Sfty SW 600V N4X SS

Manufacturer Information

Brand	Eaton
GTIN	00782113206899
Manufacturers Part Number	DH364UWK
UPC	782113206899

Taxonomies, Classifications, and Categories

Category Description	DISCONNECTS
Type	Non-Fusible Safety Switch



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

201 South Persimmon Street
77375-6855, TX Tomball
Phone: 281-357-5300
Fax: 281-357-5005

Packaging

Carton	1
Weight Per each	61

Uses, Certifications, and Standards

Application	Elec Assemblies, Panels & OEM - Electrical Assemblies, Panels and OEMsCommercial / Institutional Buildings / Structures - Power Distribution and Controls
nema rating	4X
standard	UL Listed,NEC 230.62 (C) Compliant Barrier