


# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

9172 E Florentine Road Unit 9 86314-0000, AZ Prescott Valley Phone: 928-356-1174 Fax: 480-426-8084





Size

## **DVCL153PIV Diva 150W Led 3WAY Ivory** Lutron

| Catalog Number              | DVCL153PIV   |
|-----------------------------|--|
| Manufacturer                | Lutron   |
| Description                 | Diva Led+ Dimmer - Gloss Finish, Led, Incandescent/Halogen, 3-Way/Single-Pole, 150W Led or 600W Inc/Hal In Ivory |
| Weight per unit             | 0.2500 (lbs/each)  |
| Product Category            | Lighting Dimmers   |
| eatures                     |  |
| actuator                    | Paddle Switch  |
| connection                  | Wire Leads   |
| Connection Type             | Wire Leads   |
| insulation                  | Plastic  |
| Material                    | Plastic/Metal  |
| media                       | Yes  |
| Poles                       | 1  |
| Switch Type                 | Paddle Switch  |
| Voltage Rating              | 120  |
| Wattage                     | 600  |
| laterial, Color, and Finish |  |
| Color                       | lvory  |
| Finish                      | Gloss  |
| imensions and Weight        |  |

4.69 x 2.94;119 x 75



# ELLIOTT ELECTRIC SUPPLY 9172 E Florentine Road Unit 9 86314-0000, AZ Prescott Valley Phone: 928-356-1174 Fax: 480-426-8084

| - |    |              |                | •            |    |
|---|----|--------------|----------------|--------------|----|
|   | es | ^rı          | nt             | $\mathbf{I}$ | nc |
|   | _  |              |                |              |    |
| _ | v  | <b>v</b> ı . | $\sim$ $\iota$ |              |    |
|   |    |              |                |              |    |

| Description            | DIVA 150W LED 3WAY IVORY  |
|------------------------|---|
| extra long description | LUT DVCL-153P-IV DIVA CFL/LED BOXED   |
| Features               | The Diva LED+ dimmer switch provides optimal dimming performance of LED bulbs. This dimmer switch works with up to 150-Watt of dimmable LED/CFL or 600-Watt of incandescent/halogen, allowing you to control multiple bulb types on the same circuit. It is designed to control a broad range of dimmable LED and CFL bulbs from a variety of brands including Philips, Cree, GE, EcoSmart and Lighting Science. The Diva dimmer switch features a paddle switch to turn your lights off or on returning the lights to your fav |
| Long Description       | Diva LED+ Dimmer - Gloss Finish, LED, Incandescent/Halogen, 3-way/single-pole, 150W LED or 600W inc/hal in ivory  |
| Product Type           | Diva CFL/Led Boxed Ivory  |
| Special Features       | Controls 150 W dimmable LED/CFL (screw-base), 600 W incandescent, or halogen loads. Paddle turns on/off. Slide up to brighten, down to dim. Provides reliable dimming of dimmable LEDs/CFLs, as well as halogens and incandescents.   |
| nufacturar Information |   |

#### **Manufacturer Information**

| Brand                     | Lutron         |  |
|---------------------------|----------------|--|
| GTIN                      | 00027557003032 |  |
| Manufacturers Part Number | DVCL-153P-IV   |  |
| UPC                       | 027557003032   |  |

## **Taxonomies, Classifications, and Categories**

| Category Description | Residential dimmers, motion sensors, controls, & photo cells |
|----------------------|--|
| Туре                 | Dimmer, 3-way/single-pole                                    |

## **Packaging**

| Carton          | 1    |  |
|-----------------|------|--|
| Package         | 24   |  |
| Weight Per each | 0.25 |  |



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

9172 E Florentine Road Unit 9 86314-0000, AZ Prescott Valley Phone: 928-356-1174 Fax: 480-426-8084

### **Uses, Certifications, and Standards**

| Application              | Lighting Control |  |
|--------------------------|------------------|--|
| Enclosure                | Plastic          |  |
| environmental conditions | Indoor use only  |  |
| Mounting                 | WALLBOX          |  |
| Operating Temperature    | 32 to 104        |  |
| standard                 | UL, CSA, NOM     |  |