



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

E30.125BK6P Thin-Wall Heat Shrink Tubing, 1/8" , BK *Minnesota Mining (3M)*

Catalog Number	E30.125BK6P
Manufacturer	Minnesota Mining (3M)
Description	3M™ Heat Shrink Tubing Eps-300 Is A Dual Wall Tubing Provides The Advantage Of An Integral, Adhesive Lined Construction. This Flame Retardant Tubing With A 3:1 Shrink Ratio Offers Insulation For 600V Rated Applications. The Flexible Polyolefin Construction Features An Internal Layer Of Thermoplastic Adhesive, Which Offers Moisture Seal Protection In Automotive and Marine Applications.
Weight per unit	0.0050 (lbs/each)
Product Category	Splicing & Terminating Kits

Descriptions

Description	THIN-WALL HEAT SHRINK TUBING, 1/8" , BK
extra long description	3M 7010399008 3M™ Thin-Wall Heat Sh
Features	3M™ Heat Shrink Tubing EPS-300 is color coded for quick and easy identification of the wire. It provides a skintight fit and strain relief protection for electronic components, wire splices, wire bundles and harness breakouts. This flame retardant tubing has a heat shrinkable outer wall that is irradiation cross linked for abrasion resistance and helps to maintain the high flow as well as good adhesion characteristics. When the tubing cools down, it forms a permanent, water resistant barrier. It withstands
Long Description	3M™ Heat Shrink Tubing EPS-300 is a dual wall tubing provides the advantage of an integral, adhesive lined construction. This flame retardant tubing with a 3:1 shrink ratio offers insulation for 600V rated applications. The flexible polyolefin construction features an internal layer of thermoplastic adhesive, which offers moisture seal protection in automotive and marine applications.
Product Type	3M™ Thin-Wall Heat Shrink Tubing Eps-300
Special Features	Adhesive Lined Flexible Polyolefin

Manufacturer Information

Brand	3M
GTIN	00051128601310
Manufacturers Part Number	E30.125BK6"P
UPC	051128601310

Taxonomies, Classifications, and Categories

Category Description	HEAT/COLD SHRINK
Type	Dual Wall (Adhesive Lined)



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Packaging

Carton 10

Weight Per each 0.005

Uses, Certifications, and Standards

standard UL, ABS, CSA