

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



E30.188BK6"P Thin-Wall Heat Shrink Tubing, BK, 3/16-6" *Minnesota Mining (3M)*

| Code la m Name la m | F20 100DV/IID |
|------------------------------------|---|
| Catalog Number | E30.188BK6"P |
| Manufacturer | Minnesota Mining (3M) |
| Description | 3M™ Heat Shrink Tubing Eps-300 Is A Dual Wall Tubing Provides The Advantage Of An Integral, Adhesive Lined Construction. This Flame Retardant Tubing With A 3:1 Shrink Ratio Offers Insulation For 600V Rated Applications. The Flexible Polyolefin Construction Features An Internal Layer Of Thermoplastic Adhesive, Which Offers Moisture Seal Protection In Automotive and Marine Applications. |
| Weight per unit | 0.1000 (lbs/each) |
| Product Category | Splicing & Terminating Kits |
| Descriptions | |
| Description | THIN-WALL HEAT SHRINK TUBING, BK, 3/16-6" |
| extra long description | 3M 7010350254 3M™ Thin-Wall Heat Sh |
| Features | 3M™ Heat Shrink Tubing EPS-300 is color coded for quick and |
| | easy identification of the wire. It provides a skintight fit and |
| | strain relief protection for electronic components, wire splices, |
| | wire bundles and harness breakouts. This flame retardant tubing has a heat shrinkable outer wall that is irradiation cross linked for |
| | abrasion resistance and helps to maintain the high flow as well as |
| | good adhesion characteristics. When the tubing cools down, it |
| | forms a permanent, water resistant barrier. It withstands |
| Long Description | 3M™ Heat Shrink Tubing EPS-300 is a dual wall tubing provides |
| | the advantage of an integral, adhesive lined construction. This |
| | flame retardant tubing with a 3:1 shrink ratio offers insulation for |
| | 600V rated applications. The flexible polyolefin construction |
| | features an internal layer of thermoplastic adhesive, which offers |
| Product Type | moisture seal protection in automotive and marine applications. 3M™ Thin-Wall Heat Shrink Tubing Eps-300 |
| Special Features | Adhesive Lined Flexible Pilyolefin |
| Manufacturer Information | |
| Brand | 3M |
| GTIN | 00051128600672 |
| Manufacturers Part Number | E30.188BK6"P |
| UPC | 051128600672 |
| Taxonomies, Classifications, and C | Categories |
| Category Description | <u> </u> |
| outogory bosoription | HEAT/COLD SHRINK |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

| Packaging | |
|-------------------------------------|--------------|
| Carton | 10 |
| Weight Per each | 0.1 |
| Uses, Certifications, and Standards | |
| standard | UL, ABS, CSA |