



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

425 East Germann Road Suite 101
85297-0000, AZ Gilbert
Phone: 602-325-9757
Fax: 602-325-9758



E65SMPP050HLD Photo Sensor, Perfectprox, *Eaton Corp*

Catalog Number	E65SMPP050HLD
Manufacturer	Eaton Corp
Description	Eaton SM Series Rectangular Body Photoelectric Sensor, Right Angle, Sensor Dist 2 In., 100 Ma Max DC, NPN and PNP Open Collector, 100 Ma At 30 VDC, 4 Pin M12 Connector, 10-30 VDC Input, Background Suppression
Weight per unit	0.1313 (lbs/each)
Product Category	Photoelectric Sensors

Features

connection	4-pin dual key micro connector
------------	--------------------------------

Dimensions and Weight

Height	1.29
Length	2.17
Width	1.63

Descriptions

Description	PHOTO SENSOR,PERFECTPROX,
extra long description	ETN E65-SMPP050-HLD PHOTO SENSOR,PE
Features	The SM series provides high performance and ease of use in an economical, compact package. A sensor can have the greatest performance in the world, but if it is slightly misaligned or the target is positioned at the wrong range, you will have reliability problems sooner or later. TargetLock not only simplifies sensor setup but visually confirms your sensor is positioned to operate with the highest possible reliability. In addition, TargetLock provides diagnostic information during use to inform you of impe
Long Description	Eaton SM Series Rectangular Body Photoelectric Sensor, Right Angle, Sensor dist 2 In., 100 mA max DC, NPN and PNP Open Collector, 100 mA at 30 Vdc, 4 Pin M12 Connector, 10-30 Vdc input, Background Suppression
Product Type	Photo Sensor, Perfectprox, 2", DC, Con., LT

Manufacturer Information

Brand	Eaton
GTIN	00782114786468
Manufacturers Part Number	E65-SMPP050-HLD
UPC	782114786468

Taxonomies, Classifications, and Categories

Type	Compact photoelectric sensors
------	-------------------------------



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

425 East Germann Road Suite 101
85297-0000, AZ Gilbert
Phone: 602-325-9757
Fax: 602-325-9758

Packaging

Carton	1
Weight Per each	0.1313

Uses, Certifications, and Standards

Application	Elec Assemblies, Panels & OEM - Electrical Assemblies and OEMs - Other
Operating Temperature	-13° to 131°F (-25° to 55°C)
standard	cUL Listed,UL Listed,CE Marked