


ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1810 N. Interstate 35 E 75134-0000, TX Lancaster Phone: 469-913-1947 Fax: 469-913-1948





Special Features

EDSC218 3/4" 1G 2P Sel Switch Encl *Crouse-Hinds*

Crouse-rimus	
Catalog Number	EDSC218
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Eds Snap Switch Control Station, 20A, With Switch, With Two 3/4" Hubs, Feraloy Iron Alloy, 1, Single-Gang, Two-Pole, 120-277V, Factory Sealed, Through Feed, Two-Pole, 3/4", 120-277 Vac
Weight per unit	8.5 (lbs/each)
Product Category	Selector Switch Complete Assem
Features	
amperage rating	20A
dimensions	5.0600 IN X 3.5000 IN X 5.8750 IN
Material	FERALOY IRON ALLOY
Poles	Two-pole
Voltage Rating	120-277 VAC
Dimensions and Weight	
Size	5-7/8 In Length X 3-1/2 In Width X 2-11/16 In Height
Descriptions	
Description	3/4" 1G 2P SEL SWITCH ENCL
extra long description	CRS-H EDSC218 EDS FS GENERAL USE SN
Features	New EDSX series available with NEMA 4X protection for Class I, Division 2 hazardous areas. EDS/EDSX and EFD snap switches are used with magnetic starters or contactors for control of motors. Snap switch control stations are factory sealed to prevent arcing of the enclosed device from causing ignition of a hazardous atmosphere external to the enclosure. Factory sealing eliminates the need for external seals, simplifying installation and reducing material and labor costs.
Long Description	Eaton Crouse-Hinds series EDS snap switch control station, 20A, With switch, With two 3/4" hubs, Feraloy iron alloy, 1, Single-gang, Two-pole, 120-277V, Factory sealed, Through feed, Two-pole, 3/4", 120-277 Vac
Product Type	Eds FS General Use Snap Switches
0 115 1	

Factory sealed



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1810 N. Interstate 35 E 75134-0000, TX Lancaster Phone: 469-913-1947

Fax: 469-913-1948

Manufacturer Informatio

Brand	Eaton	
GTIN	00782274765280	
Manufacturers Part Number	EDSC218	
UPC	782274765280	

Taxonomies, Classifications, and Categories

Category Description	STANDARD DUTY PUSHBUTTONS (10250H-)
Туре	Snap switch control station

Packaging

···g····g	
Carton	1
Weight Per each	8.5

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Facility: Power Distribution and Control
Enclosure	NEMA 3/7B/7C/7D/9E/9F/9G
standard	UL 1203, CSA C22.2