

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1011 First Place Blvd 73099-0000, OK Yukon Phone: 405-265-8424 Fax: 405-494-4041



EN1022 6 X 4 Basic Value Combo Kit Pass & Seymour/Legrand

Catalog Number	EN1022
Manufacturer	Pass & Seymour/Legrand
Description	Kit Includes A 14" Enclosure and A 6X4 Basic Combination Module (364400-04) Allowing Distribution Of Up to Six Telecom Outlets With Up to Four Lines Each and Incoming Video Signals to Up to Four Television Outlets. The Kit Features 18" Of Unused Rail Spac
Weight per unit	·
Product Category	
Features	
connection	110 Punchdown and F
Material	CRS
Number of Ports	6 Telecom x 4 Video
Port Type	110 Punchdown and F
Material, Color, and Finish	
Color	White/Black
Dimensions and Weight	
Height	14.1
Length	3.7
Width	14.3
Descriptions	
Description	6 X 4 BASIC VALUE COMBO KIT
extra long description	OnQ EN1022 ONQ 14 ESC BASIC 6X4 COM
Long Description	Kit includes a 14" enclosure and a 6x4 Basic Combination Module (364400-04) allowing distribution of up to six telecom outlets with up to four lines each and incoming video signals to up to four television outlets. The Kit features 18" of unused rail spac
Product Type	Onq 14 Esc Basic 6X4 Combo
Special Features	Space-saving combination module distributes telephone and video signals. UL Listed Enclosure can be either surface mount or flush mount. Integrated ground screw. Central hub for distribution and management of incoming services. Features 18" of unused rail



Availability

ELLIOTT ELECTRIC SUPPLY 1011 First Place Blvd 73099-0000, OK Yukon Phone: 405-265-8424

We Deliver...Lower Cost, Quality Products, & Personal Service

Fax: 405-494-4041

Manufacturer Information				
Brand	Legrand On-Q			
GTIN	00804428022817			
Manufacturers Part Number	EN1022			

Manufacturers Part Number	EN1022
UPC	804428022817

Taxonomies, Classifications, and Categories		
Category Description	Datacom Wiring Devices and Accessories	
Туре	Telecom/Video Module w/Enclosure	

Status	Inactive	
Packaging		

Carton	1
Weight Per each	0

Uses, Certifications, and Standards		
Application	Residential	
environmental conditions	90% Relative Humidity (Non-Condensing)	
Mounting	Enclosure (Included)	
Operating Temperature	0 TO 55 DEG C	