

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

500 Rapides Drive 71457-0000, LA Natchitoches Phone: 318-352-7414 Fax: 318-352-4100



EYD216 Drain Seal *Crouse-Hinds*

Crouse-minus	
Catalog Number	EYD216
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Eyd Conduit Sealing Fitting With Drain, Male and Female, Feraloy Iron Alloy and/or Ductile Iron, Vertical Only, Group B Rated, 3/4"
Weight per unit	1.9 (lbs/each)
Product Category	Sealing Bodies
Features	
connection	Female Threaded, Female Threaded
dimensions	1.5000 IN X 1.5000 IN X 3.6900 IN
Material, Color, and Finish	
Finish	Untreated
Descriptions	
Description	DRAIN SEAL
extra long description	CRS-H EYD216 3/4 NPT GRP B MALE/FEM
Features	In addition to restricting the passage of gases, vapors or flames from one portion of the electrical installation to another, Crouse-Hinds series EYD and EZD drain sealing fittings prevent accumulation of condensate above the seal. They are installed in vertical conduit runs and at low points in conduit systems.
Long Description	Eaton Crouse-Hinds series EYD conduit sealing fitting with drain, Male and female, Feraloy iron alloy and/or ductile iron, Vertical only, Group B rated, 3/4"
Product Type	3/4 NPT GRP B Male/Fem Iron Drain Seal
Special Features	With Drain, Vertical Position
Manufacturer Information	
Brand	EATON CROUSE-HINDS SERIES
GTIN	00782274365176
Manufacturers Part Number	EYD216
UPC	782274365176
Taxonomies, Classifications, and C	Categories
Category Description	HAZARDOUS LOCATION FITTINGS
Туре	Conduit sealing fitting with drain

Packaging

Carton	1	
Package	5	
Weight Per each	1.94	

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

500 Rapides Drive 71457-0000, LA Natchitoches Phone: 318-352-7414 Fax: 318-352-4100

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Enclosure	Class I Div 1 2 Group C D, Class II Div 1 2 Group F G, Class III
standard	UL 886, CSA C22.2