


## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

4281 Crawford Dr. 79602, TX Abilene Phone: 325-793-1570





## **EYS2 3/4" Male & Female Hub Vertical Seal Off** *Crouse-Hinds*

Crouse-Hinds	
Catalog Number	EYS2
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Eys Conduit Sealing Fitting, Female, Feraloy Iron Alloy and/or Ductile Iron, Vertical Only, Group B Rated, 3/4"
Weight per unit	1.3 (lbs/each)
Product Category	Sealing Bodies
Features	
connection	Female Threaded, Female Threaded
dimensions	1.5000 IN X 1.5000 IN X 3.7500 IN
Material, Color, and Finish	
Finish	Electrogalvanized With Aluminum Acrylic Painted
Descriptions	
Description	3/4" MALE & FEMALE HUB VERTICAL SEAL OFF
extra long description	CRS-H EYS2 3/4 NPT THRU FEM CST IRO
Features	Crouse-Hinds series EYS and EZS explosionproof sealing fittings restrict the passage of gases, vapors or flames from one portion of the electrical installation to another, limit explosions to the sealed off enclosure, and limit pre-compression or "pressure piling" in conduit systems. EYS sealing fittings are available for installation in either vertical only or in both horizontal or vertical positions. They are available in a variety of materials, including Feraloy iron alloy and/or ductile iron, copper-
Long Description	Eaton Crouse-Hinds series EYS conduit sealing fitting, Female, Feraloy iron alloy and/or ductile iron, Vertical only, Group B rated, 3/4"
Product Type	
Special Features	West Design
Manufacturer Information	
Brand	Eaton
GTIN	00782274377506
Manufacturers Part Number	EYS2

## Taxonomies, Classifications, and Categories

Category Description	HAZARDOUS LOCATION FITTINGS
Туре	Conduit sealing fitting



## ELLIOTT ELECTRIC SUPPLY 4281 Crawford Dr. 79602, TX Abilene Phone: 325-793-1570 Fax: 325-692-9649

Packaging	
Carton	5
Package	50
	1.28
Uses, Certifications, and Standards	
Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Enclosure	Class I Div 1 2 Group A B C D, Class II Div 1 Group E F G, Class II
	Div 2 Group F G, Class III
standard	UL 886, CSA C22.2