



EYS6 2" Male & Female Hub Vertical Seal Off

Crouse-Hinds

Catalog Number	EYS6
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Eys Conduit Sealing Fitting, Female, Feraloy Iron Alloy and/or Ductile Iron, Vertical or Horizontal, 2"
Weight per unit	5.2 (lbs/each)
Product Category	Sealing Bodies

Features

connection	Male Threaded, Female Threaded
dimensions	4.7000 IN X 3.6000 IN X 6.6000 IN

Material, Color, and Finish

Finish	Electrogalvanized With Aluminum Acrylic Painted
--------	---

Descriptions

Description	2" MALE & FEMALE HUB VERTICAL SEAL OFF
extra long description	CRS-H EYS6 2 NPT FEM CST IRON VERT/
Features	Crouse-Hinds series EYS and EZS explosionproof sealing fittings restrict the passage of gases, vapors or flames from one portion of the electrical installation to another, limit explosions to the sealed off enclosure, and limit pre-compression or "pressure piling" in conduit systems. EYS sealing fittings are available for installation in either vertical only or in both horizontal or vertical positions. They are available in a variety of materials, including Feraloy iron alloy and/or ductile iron, copper-
Long Description	Eaton Crouse-Hinds series EYS conduit sealing fitting, Female, Feraloy iron alloy and/or ductile iron, Vertical or horizontal, 2"
Product Type	2 NPT Fem CST Iron Vert/Horz Seal FTG
Special Features	Horizontal/Vertical Position

Manufacturer Information

Brand	EATON CROUSE-HINDS SERIES
GTIN	00782274377902
Manufacturers Part Number	EYS6
UPC	782274377902

Taxonomies, Classifications, and Categories

Category Description	HAZARDOUS LOCATION FITTINGS
Type	Conduit sealing fitting

Packaging

Carton	1
Package	10
Weight Per each	5.15



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

430 South Fletcher
75951-0000, TX Jasper
Phone: 409-489-0056
Fax: 409-489-0059

Uses, Certifications, and Standards

Application

Ind Facilities & Factories - Industrial Facilities/Factories - Other

Enclosure

CLASS I DIV 1 2 GROUP C D, CLASS II DIV 1 2 GROUP E F G, CLASS

standard

III

UL 886, CSA C22.2