

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

204 Lake Road 76426-0000, TX Bridgeport Phone: 940-683-5740 Fax: 940-683-5299



EYSR4 1-1/4" Cond Seal Crouse-Hinds

○ 5	
Catalog Number	EYSR4
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Eysr Retrofit Sealing Fitting, Feraloy Iron Alloy, 1-1/4"
Weight per unit	5.6 (lbs/each)
Product Category	Sealing Bodies
Features	
dimensions	5.0000 IN X 3.0000 IN X 3.3800 IN
Material, Color, and Finish	
Finish	Electrogalvanized With Aluminum Acrylic Painted
B 1 11	

Descriptions

Description	1-1/4" COND SEAL
extra long description	CRS-H EYSR4 1 1/4 RETROFIT SEALING
Features	Crouse-Hinds series EYSR retrofit sealing fittings are installed in rigid metal conduit systems in Class I, Division 2 hazardous locations to replace installed Eaton's Crouse-Hinds series EYS or EYD sealing fittings. EYSRs allow the replacement to be done without disassembly of the conduit system, and they can be installed in vertical or horizontal positions, indoors or outdoors. As with all sealing fittings, EYSRs restrict the passage of gases, vapors or flames from one portion of the electrical install
Long Description	Eaton Crouse-Hinds series EYSR retrofit sealing fitting, Feraloy iron alloy, 1-1/4"
Product Type	1 1/4 Retrofit Sealing FTG 5 X 3 3/8 X 3
Special Features	Horizontal/Vertical Position

Manufacturer Information

Brand	EATON CROUSE-HINDS SERIES
GTIN	00782274793399
Manufacturers Part Number	EYSR4
UPC	782274793399

Taxonomies, Classifications, and Categories

Category Description	HAZARDOUS LOCATION FITTINGS
Туре	Retrofit sealing fitting

Packaging

99		
Carton	1	
Weight Per each	5 5999	
	VIV , , , ,	

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

204 Lake Road 76426-0000, TX Bridgeport Phone: 940-683-5740 Fax: 940-683-5299

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Enclosure	Class I Div 1 2 Group C D, Class II Div 1 2 Group E F G
standard	UL 886, CSA C22.2