

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Weight Per each

EZB2060R Ez Box 20"W X 60"H, Unpainted Galvanized Eaton Corp

Catalog Number	EZB2060R	
Manufacturer	Eaton Corp	
Description	Eaton BR Thermal Magnetic Circuit Breaker, Type BR 1-Inch Plug-On Circuit Breaker, 20 A, 10 Kaic, Single-Pole, 120/240V, BR #14-4 Awg Cu/Al, Q1, Type BR Loadcenters	
Weight per unit	54.0 (lbs/each)	
Product Category	1 Pole Standard Trip Plug-In	
eatures		
dimensions	2.5000 IN X 1.0000 IN X 3.0000 IN	
interrupt rating	10 kAIC	
Poles	1	
Voltage Rating	120/240 V	
Descriptions		
Description	EZ BOX 20"W X 60"H, UNPAINTED GALVANIZED	
extra long description	ETN BR120 Type BR Breaker 20A/1 Pol	
Features	Eaton's BR circuit breakers are used in indoor and outdoor BR	
	loadcenters, spa panels, meter breakers and sub panels. They ar designed for a wide range of applications such as high short-circuit interrupt, series rating combinations with upstream main breakers, thermal magnetic, AFCI, GFCI, equipment protection and dual function AF/GF.	
Long Description	Eaton BR thermal magnetic circuit breaker, Type BR 1-Inch plug-on circuit breaker, 20 A, 10 kAIC, single-pole, 120/240V, BR, #14-4 AWG Cu/AI, Q1, Type BR loadcenters	
Product Type	Type BR Breaker 20A/1 Pole 120/240V 10K	
Manufacturer Information		
Brand	Eaton Corp	
GTIN	00786676362108	
Manufacturers Part Number	BR120	
UPC	786676362108	
axonomies, Classifications, and (Categories	
Category Description		
Туре		
ackaging		
Carton	1	

54

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses,	Certifications,	and Standards
-------	-----------------	---------------

	anda do
Application	Generation - Renewable Energy - Alternative EnergyGeneration -
	Conventional Energy - Conventional EnergyOtherMarine Vessels
	and Equipment - Marine Vessels and Equipment -
	OtherDatacenters - IT Space: CI and Hyper Converged
standard	UL 489, Federal Specifications Classification W-C375