



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

411 Autumn Street  
71901-0000, AR Hot Springs  
Phone: 501-762-8210  
Fax: 501-762-8211



## **F1.5X1.5WH6 1-1/2X1-1/2X72" WHT NM Slot Duct** *Panduit Corporation*

Catalog Number	F1.5X1.5WH6
Manufacturer	Panduit Corporation
Description	The F1.5X1.5WH6 Panduct Lead-Free PVC Narrow Slot Wiring Duct Features A Narrow Slot/Finger Design That Closely Matches The Spacing Of High-Density Components. Upper and Lower Scorelines Allow For Easy Finger/Sidewall Section Removal. UI 94 Flame Class Of V-0 With A UI Recognized Continuous-Use Temperature Up to 122°F (50°C). Mounting Holes Provided. Lead-Free PVC.1.5" X 1.5" (38.1 MM X 38.1 MM) and 6' (1.83 M) Long. Cover Sold Separately. Color White.
Weight per unit	0.1730 (lbs/each)
Product Category	Ducts, Raceways, Runways, Tray

### **Features**

connection	Mounting Holes
media	Yes

### **Material, Color, and Finish**

Color	White
-------	-------

### **Dimensions and Weight**

Height	1.62
Length	NA
Size	1.50 x 1.50
Width	1.75

### **Descriptions**

Description	1-1/2X1-1/2X72" WHT NM SLOT DUCT
extra long description	PAN F1.5X1.5WH6 Panduct® F1.5X1.5WH
Long Description	The F1.5X1.5WH6 Panduct Lead-Free PVC Narrow Slot Wiring Duct features a narrow slot/finger design that closely matches the spacing of high-density components. Upper and lower scorelines allow for easy finger/sidewall section removal. UL 94 flame class of V-0 with a UL recognized continuous-use temperature up to 122°F (50°C). Mounting holes provided. Lead-free PVC.1.5" x 1.5" (38.1 mm x 38.1 mm) and 6' (1.83 m) long. Cover sold separately. Color White.
Product Type	Panduct® F1.5X1.5WH6 Base Wiring Duct



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

411 Autumn Street  
71901-0000, AR Hot Springs  
Phone: 501-762-8210  
Fax: 501-762-8211

## Manufacturer Information

Brand	PANDUIT
GTIN	00074983375264
Manufacturers Part Number	F1.5X1.5WH6
UPC	074983375264

## Taxonomies, Classifications, and Categories

Category Description	WIRE DUCT AND COVERS
Type	Base Wiring Duct

## Availability

minimum qty	6
-------------	---

## Packaging

Carton	6
Package	120
Weight Per foot	0.173

## Uses, Certifications, and Standards

Application	Narrow slot/finger design provides more slots to fit the spacing of high-density terminal block applications
standard	RoHS Compliant, UL Recognized, CE Compliant, BABA Compliant