



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



F25T8SP30ECO 25W T8 36" 3000K 78 Cri Bi-Pin Energy Saving

Ge By Current Lamps

| | |
|------------------|---|
| Catalog Number | F25T8SP30ECO |
| Manufacturer | Ge By Current Lamps |
| Description | Ge Ecolux®, 25 WTT, 2080 LM, 3000 KV, 78 Cri, 1 In Diameter, 35.78 In Length, Medium Bi-Pin (G13) Base, 30000 HR Average Life |
| Weight per unit | 0.3500 (lbs/each) |
| Product Category | Linear Fluorescent Straight La |

Features

| | |
|--------------|---------------------|
| average life | 30000.0 |
| Base | Medium Bi-Pin (G13) |
| lumens | 2080.0 |
| Wattage | 25.0 |

Material, Color, and Finish

| | |
|-----------------------------|--------|
| color rendering index (cri) | 78.0 |
| color temperature | 3000.0 |

Dimensions and Weight

| | |
|----------|-------|
| Diameter | 1.0 |
| Length | 35.78 |

Descriptions

| | |
|------------------------|---|
| Description | 25W T8 36" 3000K 78 CRI BI-PIN ENERGY SAVING |
| extra long description | GEL F25T8/SP30/ECO 45750 FLUORESCEN |
| Long Description | GE Ecolux®, 25 WTT, 2080 LM, 3000 KV, 78 CRI, 1 IN Diameter, 35.78 IN Length, Medium Bi-Pin (G13) Base, 30000 HR Average Life |
| Product Type | 45750 Fluorescent |

Manufacturer Information

| | |
|---------------------------|--------------------------------|
| Brand | GE Current, a Daintree company |
| GTIN | 00043168457507 |
| Manufacturers Part Number | F25T8/SP30/ECO |
| UPC | 043168457507 |

Taxonomies, Classifications, and Categories

| | |
|----------------------|-------------|
| Category Description | Fluorescent |
|----------------------|-------------|

Packaging

| | |
|-----------------|------|
| Carton | 1 |
| Weight Per each | 0.35 |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Uses, Certifications, and Standards

Application

Full Wattage